

RCL-50B //

Remote Control Searchlight 80,000 Candela

Internal elevation mechanism provides pitch control of spotlight beam; protects elevation mechanism from weather

Includes fingertip remote control Point Pad™; up to three remote Point Pad™ units may be installed on system; surface/flush mount options included

Exclusive XRCiZ™ feature rotates and moves light assembly every 30 days from activation to keep all bearing surfaces free of corrosion and all electrical contacts functional

Salt water resistant construction with nylon and phenolic washers, aluminized stainless steel screws with insulating lubricant

Wiring harness 12ft. (3.65 m)

Application: Small to mid-size pleasure, small commercial crafts

Specifications

Part Number	1939.3
Size	8.4 x 6 x 8 in (21.3 x 15.2 x 21.3 cm); 4.75" diameter (120.7 cm)
Weight	6.2 lbs (2.8 kg)
Material	Aluminum
Color	White
Operation	Remote controlled Point Pad™
Beam Angle	7°
Elevation Angle	20° up, 20° down
Rotation	360° continuous
Rotation Speed	15° per second,
Elevation Speed	6° per second
Lamp	High intensity 55W Halogen
Accessories	Secondary Point Pad™ (P/N 9282.3) Replacement lamps (P/N 6002)
Footprint Diameter	4.75" (120.7 mm)
Limited Warranty	1 Year
Carton Dimensions	12.5" x 8" x 11.5" (32 x 20 x 29 cm)
Carton Weight	9 lbs (4.0 kg)



THE SCIENCE  OF SURVIVAL

COBHAM

www.acrelectronics.com

We build quality products knowing they are used to save lives.

Trademarks are the property of their respective owners. ©ACR Electronics, Inc., a Cobham plc company. All rights reserved. Ongoing product improvements may change product specifications without notice.

ACR Electronics, Inc., is registered by UL to ISO 9001:2000

United States
5757 Ravenswood Rd.
Ft Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1 (954) 981-3333
Fax: +1 (954) 961-4403

European Office
1 Rose Cottages, Pitmore Lane
Sway, Lymington
Hampshire SO41 6BX
United Kingdom
Telephone: +44 1590 683828
Fax: +44 1590 683828

Rev: 02/09