C-Strobe W

Life Preserver Emergency Signaling Strobe

Product No. 3959 Carded, 3958 Bulk

Intense strobe light visible up to 2 miles (3.2 km)

Waterproof and corrosion resistant case

New attachment pin engages top cap; prevents accidental

disassembly

Designed to meet the demands of sea, ideal for car, boat crew, campers, crisis or whenever a reliable efficient light is needed

Slim lightweight design

Comes with steel clip and adjustable Velcro strap; can be mounted on bicycle frame, pole, etc.

Size: 6 x 1.6" (15.3 x 4 cm)

Weight: 2.6 oz. (74 g)

Material: Rugged, impact and temperature resistant ABS

Color: International orange

Operation: Twist "ON/OFF" control can be operated by gloved

hands and in adverse conditions

Operational Life: More than 8 hrs @ 30°F (-1° C)

Waterproof: Up to 10ft. (3.1 m)

Accessories: P/N 9433 C-Clip Rescue Light Adapter for Inflatable

PFDs, P/N 1083 Dated Lithium Batteries

Beam Angle: Omnidirectional 360°

Visibility: High intensity strobe light is visible for up to 2 miles

(3.2 km)

Flash Rate: 60± 10 flashes per minute nominal

Lamp: Xenon flash tube

Battery Type: 2 "AA" alkaline or 1.5 lithium, release pin before

battery replacement

Certification: USCG 161.012/41/0 approved with 2 "AA" lithium

batteries; CE

Carton Dimensions: 3958—7 x 12 x 5" (18 x 30 x 13 cm)

3959—13.5 x 13.5 x 9" (34 x 134 x 23 cm)

Units per Carton: 3958—24; 3959—12

Carton Weight: 3958—4.8lbs (2.2 kg); 3959—4.5 lbs (2 kg)

Limited Warranty: 1 year

A Reference for the contract of the contract o

Shown with optional C-clip



ACR Electronics, Inc.

5757 Ravenswood Rd Fort Lauderdale, FL 33312, U.S.A. Tel Worldwide: +1(954) 981-3333 Fax: + 1(954) 961-4403 www.acrelectronics.com



ACR Electronics, Inc. is registered by UL to ISO 9001:2000