## Life Preserver Emergency Signaling Light

Product No. 3355 Carded, 3354 Bulk

Designed to meet the demands of sea, ideal for car, boat crew, campers, crisis or whenever a reliable efficient light is needed

Slim lightweight design fits easily in a pocket, hangs discreetly when attached to life vest or jacket

Attaches easily to life vest of jacket with stainless steel pin or integral lash loops and Velcro strap

Waterproof and corrosion resistant case

New attachment pin engages top cap; prevents accidental disassembly

Twist ON/OFF control can be operated by gloved hands and in adverse conditions

Adjustable wrist strap provides a means for keeping light secure

Intense incandescent light visible for up to two miles depending upon conditions; produces twinkling effect for signaling

Lens simultaneously focuses a beam of light straight ahead and a ring of light all around

Multi-faceted refracting lens intensifies light up to 20 times brighter at the horizon and 75 times at the vertical cone of light

**Size:** 5.6 x 1.3" (14.3 x 3.2 cm) **Weight:** 1.3 oz. (37 g) without batteries

Material: Rugged, impact and temperature resistant ABS

Color: International orange

Operation: Hold the light body constant and turn the lensed top to the

left to turn "ON"

Operational Life: More than 8 hrs @ 30°F (-1°C)

Waterproof: Waterproof and corrosion resistant case

Accessories: P/N 9433 C-Clip Rescue Light Adapter for Inflatable PFDs,

P/N 1083 Dated Lithium Batteries

Beam: Lens simultaneously focus a beam of light straight ahead

and a ring of light all around

**Visibility:** Intense incandescent light visible for up to 2 miles (3.2 km)

Lamp: Incandescent

**Battery Type:** 2 "AA" alkaline or 1.5 lithium, release pin before battery

replacement

**Certification:** USCG 161.012/36/0 approved lithium batteries; CE

**Carton Dimensions:** 3355—8.8 x 10.5 x 5.5" (22 x 27 x 14 cm)

3354—6 x 14.5 x 12.5" (15 x 11 x 32 cm)

**Units per Carton:** 3355—12; 3354—36

Carton Weight: 3355—3lbs (1.36 kg); 3354—5 lbs (2.27 kg)

Limited Warranty: 1 year

Patent Number: 5,237,491



Shown with optional C-clip



ACR Electronics, Inc.

5757 Ravenswood Rd Fort Lauderdale, FL 33312, U.S.A. Tel Worldwide: +1(954) 981-3333 Fax: + 1(954) 961-4403 www.acrelectronics.com



ACR Electronics, Inc. is registered by UL to ISO 9001:2000