

BATTERY SWITCH
1PUCNCVQIP CPF QRGCVRI 1P UVTWEIQPU

For use with alternators and generators rated 6-32 V.D.C. switch rating: 380 amperes continuous, 850 intermittent. Locate switch to keep battery cables short as possible. All wiring to the switch shall be performed by a SWCNKGF OCTKPGNCEVTHEICP, and in accordance with the "Fire Protection Standard For Motor Craft", P-01000 No. 302, The Standards of the American Boat and Yacht Council, Inc., and the VUEO Safety Standards for Boat Electrical Systems (33 CFR 183). If the installation requires operation at the continuous rated switch capacity (380 AMPS) in engine compartments, then the minimum cable size recommended is: 3/0 (200° C Insulation) or 4/0 (125° C Insulation). Other cable sizes may be required due to length of run and load, therefore consult engine manufacturer's recommendations for battery cable size and specifications for the installation.

- ECWQIP** - (1) Make sure connections at terminals No.1 and No. 2 are of the same polarity. Always STOP engines before switching to "OH" position.
(2) Make-Before-Break feature allows switching between 1-all-2 positions with engine running.

Erratic operation, particularly after very long periods of idleness, can be cleared by rapidly switching back and forth briskly several times with out any load connected.

NOTE: If switch is to be mounted in an area subject to corrosion, it is recommended that a liquid electrical coating be applied to the terminal connections.

The following diagrams illustrate a typical installation.

