


Assembly Instructions...

1. Mount the keel to the Otter Boat by inserting the two 1/4-20 bolts from the bottom, through the keel and then the Otter Boat. Then tightly secure the bolts with the washers and wing nuts from the top of the Otter Boat.

Note: Mount the keel on the opposite side of the Otter Boat from the tow line, with the weight pointed away from the tow line.

2. Tie a loop (off center) in the tow line with one end approximately 5 inches longer than the other end.
3. Mount the tow line to the Otter Boat by threading it through the holes on the opposite of the Otter Boat from the keel. Tie a knot in each end of the tow line, so the loop is approximately 9 inches from the front hole and approximately 14 inches from the rear hole.

Note: You can fine tune the way your Otter Boat tracks in the water by adjusting the length of either or both of the tow lines. # 55573.



How To Modify your Otter Boat For Special Applications... (Pull Copper Wire, Lead-Core & Heavy Lures)

1. Contact Big Jon Sports to purchase a "1/2 Weight Keel", Part # 55573.
2. Disassemble your Otter Boat (except for the existing keel).
3. Insert 1/4-20 bolt into the rear hole in your new 1/2 Weight Keel and the rear hole in the Otter Boat. Make sure the keel weights are pointed in the same direction.
4. Rotate the front of the 1/2 Weight Keel until the 1/2 Weight Keel is parallel to the existing keel and mark the front hole of the 1/2 Weight Keel on the bottom of the Otter Boat.
5. Remove the 1/2 Weight Keel and drill a new hole using a 1/4 in. dia. drill bit.
6. Reassemble your Otter Boat (except for the tow line).
7. On the side of the Otter Boat that you removed the tow line from, mark the locations for two new holes one inch below the existing tow line holes.
8. Drill the two new tow line holes, using a 3/16 in. dia. drill bit.

