

DO'S:

- Keep the Rim in the frame when mounting lenses.
- Only use bevel machines that are designed for wrapped lenses.
- Wrap RX compensation is done on all Wiley X frames.
- Only use polycarbonate material lenses in a Z87 stamped frame.
- All lenses must be cold snapped into Wiley X frames.
- When in doubt, please call the RX Dept. at 1.888.210.8926

Because of the specific lens requirements in our ANSI certified frames; we recommend that you only use an authorized Wiley X Lab for filling prescriptions. Filling prescription within an authentic Wiley X, Inc. frame through a non-authorized lab will void your warranty. Please contact your Wiley X, Inc. representative for a list of authorized labs.

DO'S:

- Keep the Rim in the frame when mounting lenses.
- Only use bevel machines that are designed for wrapped lenses.
- Wrap RX compensation is done on all Wiley X frames.
- Only use polycarbonate material lenses in a Z87 stamped frame.
- All lenses must be cold snapped into Wiley X frames.
- When in doubt, please call the RX Dept. at 1.888.210.8926

Because of the specific lens requirements in our ANSI certified frames; we recommend that you only use an authorized Wiley X Lab for filling prescriptions. Filling prescription within an authentic Wiley X, Inc. frame through a non-authorized lab will void your warranty. Please contact your Wiley X, Inc. representative for a list of authorized labs.

DO'S:

- Keep the Rim in the frame when mounting lenses.
- Only use bevel machines that are designed for wrapped lenses.
- Wrap RX compensation is done on all Wiley X frames.
- Only use polycarbonate material lenses in a Z87 stamped frame.
- All lenses must be cold snapped into Wiley X frames.
- When in doubt, please call the RX Dept. at 1.888.210.8926

Because of the specific lens requirements in our ANSI certified frames; we recommend that you only use an authorized Wiley X Lab for filling prescriptions. Filling prescription within an authentic Wiley X, Inc. frame through a non-authorized lab will void your warranty. Please contact your Wiley X, Inc. representative for a list of authorized labs.

DON'TS:

- When mounting lenses, do not remove the Rim from the Frame.
- Never heat a Wiley X frame.
- Do not remove the information cards that come in the case with your Wiley X frames. There is crucial information for outside labs in order to fill prescriptions within an authentic Wiley X frames to meet required ANSI standards.
- Do not cut RX lenses oversize; this will stress the frame causing it to crack over time.
- Do not put a flat lens into a wrapped frame, without the proper bevel equipment as this can splay the temples rendering it unusable.

Here at Wiley X, Inc. we know how important prescription eyewear is to you and your customer, therefore all Wiley X, Inc. eyewear has been compensated accordingly for wrap, tilt, and vertex distance to achieve superior optical quality. This may result in slight RX power differential between the RX lenses and the one you have prescribed to custom fit specific vision needs.

DON'TS:

- When mounting lenses, do not remove the Rim from the Frame.
- Never heat a Wiley X frame.
- Do not remove the information cards that come in the case with your Wiley X frames. There is crucial information for outside labs in order to fill prescriptions within an authentic Wiley X frames to meet required ANSI standards.
- Do not cut RX lenses oversize; this will stress the frame causing it to crack over time.
- Do not put a flat lens into a wrapped frame, without the proper bevel equipment as this can splay the temples rendering it unusable.

Here at Wiley X, Inc. we know how important prescription eyewear is to you and your customer, therefore all Wiley X, Inc. eyewear has been compensated accordingly for wrap, tilt, and vertex distance to achieve superior optical quality. This may result in slight RX power differential between the RX lenses and the one you have prescribed to custom fit specific vision needs.

DON'TS:

- When mounting lenses, do not remove the Rim from the Frame.
- Never heat a Wiley X frame.
- Do not remove the information cards that come in the case with your Wiley X frames. There is crucial information for outside labs in order to fill prescriptions within an authentic Wiley X frames to meet required ANSI standards.
- Do not cut RX lenses oversize; this will stress the frame causing it to crack over time.
- Do not put a flat lens into a wrapped frame, without the proper bevel equipment as this can splay the temples rendering it unusable.

Here at Wiley X, Inc. we know how important prescription eyewear is to you and your customer, therefore all Wiley X, Inc. eyewear has been compensated accordingly for wrap, tilt, and vertex distance to achieve superior optical quality. This may result in slight RX power differential between the RX lenses and the one you have prescribed to custom fit specific vision needs.

MAINTENANCE: Wiley X lenses are specially coated to offer superior abrasion resistance. Please follow below instructions to prolong the life of your lenses and keep them performing at their best:

- Clean lenses with water only.
- Do not use solvents or special cleaners.
- Use micro-fiber cleaning cloth provided to gently wipe clean.
- Never use paper products to clean and avoid wiping lens surface when dry and/or dirty as this may potentially scratch the lens.

WARNING: Wiley X brand eyewear is tested tough. However, impact resistant eyewear is not unbreakable and does not provide unlimited eye protection under all circumstances and conditions. Misused, abused, scratched and/or damaged eyewear can reduce impact protection [and void your limited warranty]. Dirty and/or wet eyewear can impair vision and reduce safety [resulting in personal injury and/or property damage]. Keep your Wiley X eyewear clean with water only. Do not use solvents or abrasives as it could scratch or damage the product reducing its effectiveness. Store your Wiley X eyewear in the protective case provided to prolong the life of the lenses. Most of all, take all appropriate precautions when wearing your Wiley X eyewear during hazardous and/or dangerous activities and conditions. Wiley X, Inc. is not responsible for personal injury, property damage or losses incurred while using Wiley X brand products.



WILEY X INC. 1.800.776.7842 // 925.243.9810 // WILEYX.COM
 7800 PATTERSON PASS ROAD, LIVERMORE CA 94550 USA
WILEY X EUROPE LLC: +45 96 93 00 45 // WILEYX.EU
 SØNDERGADE 8-10 7570 VEMB DENMARK

A3517[1]

MAINTENANCE: Wiley X lenses are specially coated to offer superior abrasion resistance. Please follow below instructions to prolong the life of your lenses and keep them performing at their best:

- Clean lenses with water only.
- Do not use solvents or special cleaners.
- Use micro-fiber cleaning cloth provided to gently wipe clean.
- Never use paper products to clean and avoid wiping lens surface when dry and/or dirty as this may potentially scratch the lens.

WARNING: Wiley X brand eyewear is tested tough. However, impact resistant eyewear is not unbreakable and does not provide unlimited eye protection under all circumstances and conditions. Misused, abused, scratched and/or damaged eyewear can reduce impact protection [and void your limited warranty]. Dirty and/or wet eyewear can impair vision and reduce safety [resulting in personal injury and/or property damage]. Keep your Wiley X eyewear clean with water only. Do not use solvents or abrasives as it could scratch or damage the product reducing its effectiveness. Store your Wiley X eyewear in the protective case provided to prolong the life of the lenses. Most of all, take all appropriate precautions when wearing your Wiley X eyewear during hazardous and/or dangerous activities and conditions. Wiley X, Inc. is not responsible for personal injury, property damage or losses incurred while using Wiley X brand products.



WILEY X INC. 1.800.776.7842 // 925.243.9810 // WILEYX.COM
 7800 PATTERSON PASS ROAD, LIVERMORE CA 94550 USA
WILEY X EUROPE LLC: +45 96 93 00 45 // WILEYX.EU
 SØNDERGADE 8-10 7570 VEMB DENMARK

A3517[1]

MAINTENANCE: Wiley X lenses are specially coated to offer superior abrasion resistance. Please follow below instructions to prolong the life of your lenses and keep them performing at their best:

- Clean lenses with water only.
- Do not use solvents or special cleaners.
- Use micro-fiber cleaning cloth provided to gently wipe clean.
- Never use paper products to clean and avoid wiping lens surface when dry and/or dirty as this may potentially scratch the lens.

WARNING: Wiley X brand eyewear is tested tough. However, impact resistant eyewear is not unbreakable and does not provide unlimited eye protection under all circumstances and conditions. Misused, abused, scratched and/or damaged eyewear can reduce impact protection [and void your limited warranty]. Dirty and/or wet eyewear can impair vision and reduce safety [resulting in personal injury and/or property damage]. Keep your Wiley X eyewear clean with water only. Do not use solvents or abrasives as it could scratch or damage the product reducing its effectiveness. Store your Wiley X eyewear in the protective case provided to prolong the life of the lenses. Most of all, take all appropriate precautions when wearing your Wiley X eyewear during hazardous and/or dangerous activities and conditions. Wiley X, Inc. is not responsible for personal injury, property damage or losses incurred while using Wiley X brand products.



WILEY X INC. 1.800.776.7842 // 925.243.9810 // WILEYX.COM
 7800 PATTERSON PASS ROAD, LIVERMORE CA 94550 USA
WILEY X EUROPE LLC: +45 96 93 00 45 // WILEYX.EU
 SØNDERGADE 8-10 7570 VEMB DENMARK

A3517[1]



RX RIM SYSTEM INSTRUCTIONS

COPYRIGHT © 2014 WILEY X, INC. ALL RIGHTS RESERVED.

WILEY X, WX, BLACK OPS, logos, tag lines and product names are trademarks or registered trademarks [marcas registradas] of Wiley X, Inc. in the U.S. and other countries. Logos © 2007-2014 Wiley X, Inc. All rights reserved.



RX RIM SYSTEM INSTRUCTIONS

COPYRIGHT © 2014 WILEY X, INC. ALL RIGHTS RESERVED.

WILEY X, WX, BLACK OPS, logos, tag lines and product names are trademarks or registered trademarks [marcas registradas] of Wiley X, Inc. in the U.S. and other countries. Logos © 2007-2014 Wiley X, Inc. All rights reserved.



RX RIM SYSTEM INSTRUCTIONS

COPYRIGHT © 2014 WILEY X, INC. ALL RIGHTS RESERVED.

WILEY X, WX, BLACK OPS, logos, tag lines and product names are trademarks or registered trademarks [marcas registradas] of Wiley X, Inc. in the U.S. and other countries. Logos © 2007-2014 Wiley X, Inc. All rights reserved.

1 REMOVE GASKET FROM FRAME

2 LENS REMOVAL [OPTION 1]



Pull Rim apart outward from top and bottom



Push out lens using thumbs

LENS REMOVAL [OPTION 2]



Hold Rim firmly at nasal



Push lens outward at nasal using thumbs

3 RIM REMOVAL DO NOT TWIST FRAME



*Note: Keep Rim in the frame when mounting lenses

with index fingers outside, secure pressure on inside of the frame nasal area.



Push outward with thumb

4 LENS/RIM RE MOUNT

The Lens/Rim will both mount back into the bezel by the follow steps: *Mount lens with Rim in frame



Insert back



Insert nasal



Snap bottom into place

This is a guideline for all WileyX "Rim System" products. High + - Rx may take additional pressure to remove/remount

1 REMOVE GASKET FROM FRAME

2 LENS REMOVAL [OPTION 1]



Pull Rim apart outward from top and bottom



Push out lens using thumbs

LENS REMOVAL [OPTION 2]



Hold Rim firmly at nasal



Push lens outward at nasal using thumbs

3 RIM REMOVAL DO NOT TWIST FRAME



*Note: Keep Rim in the frame when mounting lenses

with index fingers outside, secure pressure on inside of the frame nasal area.



Push outward with thumb

4 LENS/RIM RE MOUNT

The Lens/Rim will both mount back into the bezel by the follow steps: *Mount lens with Rim in frame



Insert back



Insert nasal



Snap bottom into place

This is a guideline for all WileyX "Rim System" products. High + - Rx may take additional pressure to remove/remount

1 REMOVE GASKET FROM FRAME

2 LENS REMOVAL [OPTION 1]



Pull Rim apart outward from top and bottom



Push out lens using thumbs

LENS REMOVAL [OPTION 2]



Hold Rim firmly at nasal



Push lens outward at nasal using thumbs

3 RIM REMOVAL DO NOT TWIST FRAME



*Note: Keep Rim in the frame when mounting lenses

with index fingers outside, secure pressure on inside of the frame nasal area.



Push outward with thumb

4 LENS/RIM RE MOUNT

The Lens/Rim will both mount back into the bezel by the follow steps: *Mount lens with Rim in frame



Insert back



Insert nasal



Snap bottom into place

This is a guideline for all WileyX "Rim System" products. High + - Rx may take additional pressure to remove/remount