


Intensifier H® Series Indoor/Outdoor Turret Camera

See Color In Almost Complete Darkness Without IR LEDs

HTINTD8H 2.8 -12mm auto iris varifocal lens, dark grey housing
HTINTD8HW 2.8 -12mm auto iris varifocal lens, white housing

Features

- 1/3" 960H ExView™ HAD CCD II
- 700 lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensify @ 512x)
- Presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- 12VDC / 24VAC dual voltage operation
- Full OSD operation and test monitor output
- 3-axis wall or ceiling mount
- External controls for zoom & focus
- EZ mount system simplifies installation
- Relay outputs for motion detection
- Weather resistant operation
- IP66 compliant
- Anti-moisture glass and circuitry eliminates fog or condensation under any weather condition
- 5 year warranty



Specifications

Image Sensor 1/3" 960H ExView™ HAD CCD II
 Resolution..... 700 TV lines
 Minimum Illumination..... 0.00002 lux
 Effective Pixels 976 (H) x 494 (V)
 Total Pixels 1020 (H) x 508 (V)
 TV System..... NTSC
 Scanning Frequency..... 15.734kHz (H) / 59.94Hz (V)
 Scanning System..... 2:1 interlace
 Synchronization..... Internal
 S/N Ratio More than 52dB
 Video Output..... CVBS: 1.0Vp-p / 75 ohms
 Electronic Shutter Speed..... 1/60 sec. - 1/120,000 sec.
 OSD..... Available
 DWDR On / Off (level adjustable)
 Backlight Compensation..... BLC / HLC / Off
 Day/Night..... Color / BW / Auto / Ext
 AGC..... High / Low / Off

White Balance ATW / Outdoor / Indoor / Manual / AWC (1,700°K – 11,000°K)
 Intensify Auto / Off (selectable 2x – 512x)
 Motion Detection..... On / Off (8 programmable zones)
 Privacy Masking On / Off (12 programmable zones)
 Speco DNR..... On / Off (level adjustable)
 Digital Zoom On / Off (1x - 16x)
 DIS..... On / Off
 Sharpness On / Off (level adjustable)
 Flip / Mirror On / Off
 Power Consumption 12VDC, 400mA / 24VAC, 170mA
 Power Supply 12VDC / 24VAC dual voltage operation (power supply not included)
 Operating Temperature..... - 4° F – 140° F
 Dimensions 4.36" (H) x 5.47" (Dia.)
 Weight 3.08 lbs.


Optional Accessories



INTPM
Pendant Mount



JB03TG
Large Round Junction Box



INTCM
Corner/Pole Adaptor (use with INTWM only)



INTWM
Wall Mount



PSW4
24VAC Power Supply



PSW5
12VDC Power Supply

