

# REFMPK315.2

INFPRV315.2



- 3.5" Color Screen
- Black chrome trim
- Rotary Encoder
- BT4 with id tagging
- Aux in
- USB input
- 3 pairs of pre-outs including separate subwoofer out
- Wired/wireless remote ready
- 2 ohm stable

INF622MLT



- 6-1/2" 2-way marine speakers (pair)
- multi-color RGB LED lights
- polypropylene cone
- bridge-mounted balanced dome tweeter
- one-piece cast polymer basket
- IPX5 rated for water resistance

INF1022MLT



- 10" 4-ohm marine subwoofer
- polypropylene cone with rubber surround
- multi-color RGB LED lights
- one-piece cast polymer basket
- IPX5 rated for water resistance
- power handling: 250 watts RMS (750 watts peak power)
- sensitivity: 89 dB
- frequency response: 25-500 Hz
- impedance: 4 ohm

REFM4555A



- **5-channel marine amplifier**
- **45 watts RMS x 4 + 320 watts RMS x 1 at 4 ohms**
- **65 watts RMS x 4 + 500 watts RMS x 1 at 2 ohms**
- **130 watts RMS x 2 bridged at 4 ohms + 500 watts**
- **Class D amp technology**
- **front and rear channels:**
  - **variable high- and low-pass filters**
- **subwoofer channel:**
  - **low-pass filter**
  - **bass boost on subwoofer**
  - **phase switch (0, 180 degrees)**

USB EXTENDER

Dipole Antenna

