




SPINFISHER™ VII



- IPX5 Sealed body and spool design
- CNC Gear Technology with brass main gear
- HT-100™ Carbon Fiber Drag Washers
- 5+1 sealed stainless steel ball bearing system
- Full Metal Body
- Superline Spool



Durability, Smoothness, and Precision is what CNC Gear™ Technology delivers. By using state of the art software and CNC machinery the drive and pinion gear are cut to exact tolerances using premium metals.



Sealed from splashes and spray, protecting key internal parts



The PENN patented line clip design makes line management easier than ever. This line clip was engineered to hold line from thin braid to large diameter leader.

Model	Material #	Mono Cap (yds/lb)	Braid Cap (yds/lb)	Bearings	Max Drag	Gear Ratio	Line Retrieve (in)	Weight (oz)
SSVII2500	1594595	175 / 8	220 / 15	6	15 lbs	6.2:1	33 in	11
SSVII3500	1594596	285 / 8	270 / 15	6	15 lbs	6.2:1	37 in	12.3
SSVII4500	1594597	320 / 10	320 / 20	6	20 lbs	6.2:1	40 in	12.8
SSVII4500BLS*	1594598	320 / 10	320 / 20	6	20 lbs	6.2:1	40 in	12.6
SSVII5500	1594599	330 / 12	380 / 30	6	25 lbs	5.6:1	39 in	19
SSVII6500	1594600	345 / 15	410 / 40	6	30 lbs	5.6:1	42 in	22.3
SSVII6500BLS*	1594601	345 / 15	410 / 40	6	30 lbs	5.6:1	42 in	21.8
SSVII7500	1594602	330 / 20	440 / 50	6	35 lbs	4.7:1	38 in	26.5
SSVII8500	1594603	310 / 30	600 / 50	6	40 lbs	4.7:1	42 in	42.2
SSVII9500	1594604	300 / 40	670 / 65	6	45 lbs	4.2:1	40 in	37.1
SSVII10500	1594605	360 / 40	780 / 65	6	50 lbs	4.2:1	43 in	38.6

*BLS - Bail-less Model