

Pacer

Cable Clamps







Cable clamps provide secure containment for many cable or harness diameters. Made from 1/2" wide nylon, they are resistant to a variety of hazards. These include: acids, oils, flame, and grease. With a single screw, you can use cable clamps to mount a variety of materials. Some of these include wires, hoses, and tubing products. Use stainless steel clamps when weight and vibration are factors. Black neoprene cushions cover the stainless steel clamps. This protects harnesses or hoses from abrasions. It also serves to dampen vibrations.



Construction

High quality Nylon 6.6 or
AISI 316 Stainless steel





Benefits

-  Reliable
-  Versatile
-  Long lasting
-  High strength
-  Easy to install
-  Dampens vibrations

Pacer is a Proud Member of:




Applications

-  Commercial Usage
-  Residential Usage
-  Industrial Usage
-  Marine Usage



STAINLESS STEEL CUSHION CLAMPS




PART NUMBER	SIZE	A (Inches)	B (Inches)	C (Inches)	D (Inches)	E (Inches)	WIDTH (Inches)	PACKAGE SIZE
BSSC04	1/4"	0.250	0.529	0.032	0.062	0.062	0.500	10, 25, 100, 2500
BSSC06	3/8"	0.375	0.592	0.032	0.062	0.062	0.500	10, 25, 100, 1700
BSSC08	1/2"	0.500	0.654	0.032	0.062	0.062	0.500	10, 25, 100, 1200
BSSC10	5/8"	0.625	0.780	0.032	0.062	0.109	0.500	10, 25, 100, 1000
BSSC12	3/4"	0.750	0.842	0.032	0.062	0.109	0.500	10, 25, 100, 1500
BSSC14	7/8"	0.875	0.889	0.032	0.062	0.109	0.500	10, 25, 100, 1200
BSSC16	1"	1.000	0.951	0.032	0.062	0.109	0.500	10, 25, 100, 1000
BSSC18	1 1/8"	1.125	1.062	0.032	0.062	0.125	0.500	10, 25, 100, 500
BSSC20	1 1/4"	1.250	1.093	0.032	0.094	0.125	0.500	10, 25, 100, 700
BSSC22	1 3/8"	1.375	1.187	0.032	0.094	0.125	0.500	10, 25, 100, 600
BSSC24	1 1/2"	1.500	1.217	0.032	0.094	0.125	0.500	10, 25, 100, 500
BSSC28	1 3/4"	1.750	1.342	0.032	0.094	0.125	0.500	10, 25, 100, 450
BSSC32	2"	2.000	1.475	0.040	0.125	0.125	0.500	10, 25, 100, 350
BSSC36	2 1/4"	2.250	1.598	0.040	0.125	0.125	0.500	5, 10, 25, 300
BSSC40	2 1/2"	2.500	1.728	0.040	0.125	0.125	0.500	5, 10, 250
BSSC44	2 3/4"	2.750	1.851	0.040	0.125	0.125	0.500	5, 10, 200
BSSC48	3"	3.000	1.976	0.040	0.125	0.125	0.500	5, 10, 175
BSSC56	3 1/2"	3.500	2.226	0.040	0.125	0.125	0.500	5, 10, 300
BSSC64	4"	4.000	2.476	0.040	0.125	0.125	0.500	5, 10, 250

APPLICATIONS: Stainless steel clamps are used for mounting wire, cable or hoses where weight and vibration are a factor.

FEATURES: *1/4" mounting hole *1/2" width for strength *Sizes from 1/4" to 4"

COMPLIANCES: *304/321 Stainless steel meets MIL-S-5059 AMS5510 *General purpose EPDM per SAE J200BC715

NYLON C-CLAMPS



NATURAL	SIZE (Inches)	A (Inches)	B (Inches)	C (Inches)	D (Inches)	E (Inches)	PACKAGE SIZE
BCCH02	1/8"	0.120	0.500	0.360	0.203	0.100	100 1000
BCCH03	3/16"	0.190	0.500	0.420	0.203	0.100	100 1000
BCCH04	1/4"	0.250	0.500	0.460	0.203	0.100	100 1000
BCCH05	5/16"	0.310	0.500	0.500	0.203	0.100	100 1000
BCCH06	3/8"	0.380	0.500	0.530	0.203	0.100	100 1000
BCCH07	7/16"	0.440	0.500	0.560	0.203	0.100	100 1000
BCCH08	1/2"	0.500	0.500	0.590	0.203	0.100	100 1000
BCCH09	9/16"	0.560	0.500	0.610	0.203	0.100	100 1000
BCCH10	5/8"	0.620	0.500	0.650	0.203	0.100	100 1000
BCCH11	11/16"	0.690	0.500	0.750	0.203	0.100	100 -
BCCH12	3/4"	0.750	0.500	0.780	0.203	0.100	100 500
BCCH13	13/16"	0.810	0.500	0.810	0.203	0.100	100 -
BCCH14	7/8"	0.870	0.500	0.840	0.203	0.100	100 500
BCCH16	1"	1.000	0.500	0.910	0.203	0.100	100 500
BCCH20	1 1/4"	1.250	0.500	1.060	0.203	0.100	100 -
BCCH24	1 1/2"	1.500	0.500	1.190	0.203	0.100	100 -

FEATURES: *Stocked in natural and black heat/UV stabilized 6/6 nylon *1/2" width for strength *Sizes from 1/8" to 1 1/2"
Mounts with a #10 screw