



MEGA LIVE 2

» FORWARD-FACING SONAR

Catch All the Action

Hallmark clarity takes another step forward in the newest iteration of Humminbird's forward-facing sonar. MEGA Live 2 gives you an incredible live look, separating fish and structure with reduced noise, improved bait tracking and image stability. Now it's easier than ever to watch your highlight reels happen. Choose how to angle your beam with three different views, each including the new TargetBoost setting that eliminates bottom interference. Then customize your live sonar feed with 15 fishing-themed color palettes optimized for clearer sonar returns. Better fishing takes a leap forward with MEGA Live 2.

FEATURES

SONAR CAPABILITY

Sonar Type: Imaging

Sonar Frequency:
1.05 CHIRP MHz

Sonar Coverage Across
Beamformed Axis: 20 degrees

Sonar Coverage Along
Beamformed Axis: 120 degrees

Sonar Away Range: 150 ft

Sonar Down Range: 150 ft

COMPATIBLE CONTROL HEADS

APEX 13

APEX 16

APEX 19

XPLORE 9 CMSI+

XPLORE 10 CMSI+

XPLORE 12 CMSI+

SOLIX 10 MSI+ G3

SOLIX 12 MSI+ G3

SOLIX 15 MSI+ G3

VIEWING MODES

Forward Mode

Landscape Mode

Down Mode

HIGHLIGHTS

15 Optimized Color Palettes

Enhanced Clarity and Detail

Custom Mounting Setup Options

TargetBoost: Enhanced Clarity, Improved Bait Tracking,
No More Bottom Interference

INCLUDED IN THE BOX

MEGA Live 2 Transducer Charger Power Cable with Choke

20' Ethernet Cable Protective Film

10' Power Cable Hardware: Mount Screws, Cable Ties

WARRANTY

2-Year Limited Warranty

MODEL

MEGA Live Sonar

710310-1 MEGA LIVE 2 UPC: 0-82324-05892-9

ELECTRICAL PLATFORM

MEMORY

NAND (MoviNAND): 16 GB

SDRAM (DDR3): 128 Mbit

SPI Flash: BOSCH

OPERATIONAL SPECIFICATIONS

Power Input: 10-20 (V)

Current Draw – Nominal: 930 (mA)

Current Draw – In-Rush: 2500 (mA)

Temperature: -20° to 70° C / -4° to 158° F

Waterproof Rating: IPX8

MECHANICAL PLATFORM

MOUNTING SYSTEM

Steerable Mount: Update with TargetLock

Shaft Mount: 1.5" with Angular Adjustment of 7.5 Degrees
and Rubber Pads Included

Landscape Mount: With Angular Adjustment of 7.5 Degrees,
Mount Adapter, Transmount Accessory and Mask

CABLES

10' Power/Serial Included

20' Ethernet Cable Included