

# COMMODORE

## On/Off Battery Disconnect Switch CM-202S

- Continuous Rating: 300A DC
- Cranking Rating: 900A DC
- Tin-Plated Copper Studs for Maximum Conductivity and Corrosion Resistance
- Case Design Allows it to be both Surface Mounted or Flush Mounted from the Rear
- Studs Accept 3/8" (10M) Ring Terminals
- Isolating Cover with 3 Snap-In Side Access Plates (Can be wired from any direction)



### Specifications

Cranking Rating: 30 sec.	900A DC
Intermittent Rating: 5 min.	500A DC
Continuous Rating:	300A
DC Terminal Stud, Tin-Plated Copper	3/8" -16 (M10)
Torque 120 in-lb (13.56 N·m) Cable Size to Meet Ratings*	4/0 AWG (120 mm <sup>2</sup> )
Maximum Voltage Rating	32 Volts DC
Ignition Protected	ISO 8846 Marine

### Caractéristiques techniques

puissance de démarrage : 30 sec.	900A DC
taux d'intermittence : 5 min.	500A DC
puissance continue :	300A
goujon de borne CC, cuivre étamé	3/8" -16 (M10)
13,56 N·m (120 in-lb) Taille du câble pour respecter les valeurs nominales* 6.	4/0 AWG (120 mm <sup>2</sup> )
tension nominale maximale	32 Volts DC
protection contre l'allumage	ISO 8846 Marine

### Multiple Installation Mode / Mode D'installation Multiple



Rear panel mounting  
Fixation sur panneau  
arrière



Front panel mounting  
Montage sur le panneau  
avant



Surface mounting  
Montage en surface

Meets or exceeds the following Standards:

**ABYC C-7 CSA C22.2 No. 4 UL 1107**  
**Ignition Protected - ISO 8846 Marine**

