

PRODUCT INFO

CSX SERIES

The all-in-one upgrade for marine refrigeration. The Dometic CSX delivers next-generation cooling performance in a compact, integrated design. With precision temperature control, fan-assisted cooling and ultra-efficient, low-GWP refrigerant, it's built to keep food and drinks fresher for longer - no matter where you sail.

ALL-IN-ONE DESIGN
FULLY INTEGRATED

FAST, EVEN COOLING
FAN-ASSISTED AIRFLOW

PRECISION CONTROL
NTC SENSOR



Mobile living made easy.

 **DOMETIC**

COOL SMARTER EXPLORE MORE

The Dometic CSX is a self-contained cooling system engineered for effortless installation and reliable performance. Ideal for volumes between 50 and 400 L, it combines a high-efficiency compressor, fan-cooled evaporator and digital temperature control in one space-saving unit. Simply drop it in, connect power, and enjoy consistent cooling without the complexity of remote couplings. With low-GWP refrigerant*, reduced power draw and a durable marine-ready build, the CSX is the smarter way to keep provisions fresh - whether you're coastal cruising or voyaging offshore.

Benefits with Dometic CSX Series

- Integrated compressor and evaporator for easy drop-in install
- Fan-assisted airflow reduces cool-down time and maintains even temperature
- Digital temperature control with high-accuracy NTC sensor
- Up to 20% lower power consumption vs. previous models
- Low-GWP refrigerant* (R1234yf) for reduced environmental impact
- Built-in LED compartment lighting for better visibility
- Compact footprint for space-restricted galleys or boxes
- Available in refrigerator or deep-freezer versions
- Electronic control with automatic defrost logic

*GWP = Global Warming Potential refers to the global warming potential should a gas be emitted into the atmosphere. The higher the GWP value, the more harmful the gas's impact on the environment.

Specifications

VOLUME RANGE	60–200 L (CSX-200) 60–150 L Freezer (CSX-FZ150) 250–400 L (CSX-400)
REFRIGERANT	R1234yf
CONTROL SYSTEM	Digital display (internal or external mount) NTC sensor
COOLING METHOD	Fan-cooled evaporator with integrated compressor
POWER SUPPLY	12/24 V DC
LIGHTING	Built-in LED compartment lighting
INSTALLATION	Drop-in, no couplings required



Mobile living made easy.



COOL SMARTER EXPLORE MORE



DOMETIC CSX SERIES TECHNICAL DATA			
MODEL	CSX200	CSX400	CSX150FZ
SKU	9630000213	9630000214	9630000215
Max. Cooling Capacity (L)	200	400	150 (Deep Freezing)
Connection Voltage	12 / 24v DC		
Power Consumption (Rated Max W)	75	77	81
Refrigerant Type	r1234yf		
Global Warming Potential (GWP)	4		
Refrigerant Quantity (g)	42	45	65
CO2 Equivalent (tCO2)	0.00017	0.00018	0.00026
Dimensions (W x H x D) (MM)			
Full Unit	257 x 350 x 225	257 x 350 x 227	414 x 415 x 400
Evaporator Side	257 x 350 x 79	257 x 350 x 79	414 x 415 x 170
Cutout	204 x 210	204 x 210	204 x 210
Weight (kg)	5.8	5.8	8.5

