

THE AQUA JET II - WASHDOWN PUMPS AND KITS

Johnson Pump Marine's new Aqua Jet II Washdown Pump is built to excel in harsh saltwater environments. This next-generation pump delivers powerful performance, smooth operation, and unmatched corrosion resistance with the flexibility today's boaters demand.

Built to Last

Engineered with a dual-layer surface treatment, E-coating followed by powder coating, Aqua Jet II is designed to withstand the toughest marine conditions. Its compact flexible bracket design allows versatile installation, while KlickTite enable tool-free inspection or assembly. The proven 5-chamber diaphragm system ensures reliable flow and quiet, efficient operation.

Common Applications:

Perfect for rugged marine use, Aqua Jet II pumps are ideal for:

- Deck and surface washdowns: bait and fish stations, cockpit, anchor, and transom clean-up
- Regulatory cleaning: supporting invasive species decontamination standards for trailered boats



**QUICK-CHANGE
ELECTRICAL
CONNECTION**



**SIMPLIFIED PUMP
MOUNTING BRACKET**



AQUA JET II FULL KIT



**AQUA JET II
HALF KIT**



FEATURES	BENEFITS/ADVANTAGES
5 Chamber Membrane Design	Self priming up to 2.5m and can run dry Quiet and pulsation-free operation compared to less chambers
Quick-Change Connection	Included harness connection requiring no cutting and splicing of wires
Pressure Switch	Automatic operation
KlickTite Port Connection	Easy installation and maintenance
Corrosion-Resistant Design	Withstands harsh conditions thanks to e-coating and powder coating
Dry-Running Ability	Reliable performance even if water levels are low
Thermal Overload Protection	Protection against overheat, extending pump life
High Torque & Rpm Motor	High pressure - 73 psi
Nitrile Rubber Membrane	Withstands raw water
Warranty	3-Years
PC-ABS Plastic Bracket	Removable pump for easy installation, maintenance, and winterization allowing for easy pump rotation
Inlet Strainer	Built-in KlickTite for easy inlet installation Protect the pump from debris and extend its service life

TECHNICAL SPECIFICATIONS

	PART NUMBER	DESCRIPTION	CAPACITY	PRESSURE CUT OFF	FUSE SIZE	MOTOR	LENGTH	WIDTH	HEIGHT	WEIGHT
REPLACEMENT PUMP	10-25013-13	AQUA JET II WD 3.5 12V	3.5 GPM	73 psi	20 A	120W	8.5"	8.27"	4.56"	5.29 lbs
	10-25014-13	AQUA JET II WD 5.2 12V	5.2 GPM	73 psi	20 A	185W	8.74"	8.23"	4.4"	5.51 lbs
	10-25014-14	AQUA JET II WD 5.2 24V	5.2 GPM	73 psi	10 A	185W	8.74"	8.23"	4.4"	5.51 lbs
HALF KIT	10-25013-03	AQUA JET II WD 3.5 12V	3.5 GPM	73 psi	20 A	120W	8.5"	8.27"	4.56"	5.29 lbs
	10-25013-04	AQUA JET II WD 3.5 24V	3.5 GPM	73 psi	10 A	120W	8.5"	8.27"	4.56"	5.29 lbs
	10-25014-03	AQUA JET WD 5.2 12V	5.2 GPM	73 psi	20 A	185W	8.74"	8.23"	4.4"	5.51 lbs
	10-25014-04	AQUA JET II WD 5.2 24V	5.2 GPM	73 psi	10 A	185W	8.74"	8.23"	4.4"	5.51 lbs
FULL PUMP KIT	10-25013-14	AQUA JET II WD 3.5 12V	3.5 GPM	73 psi	20 A	120W	8.5"	8.27"	4.56"	5.29 lbs
	10-25014-15	AQUA JET II WD 5.2 12V	5.2 GPM	73 psi	20 A	185W	8.74"	8.23"	4.4"	5.51 lbs
	10-25014-16	AQUA JET II WD 5.2 24V	5.2 GPM	73 psi	10 A	185W	8.74"	8.23"	4.4"	5.51 lbs

Diaphragm	Santoprene
Valves	Nitrile
Body	PP/PPA
Bracket	PC-ABS
Hole Pattern:	Width: 4.25" Length: 2.5" Ø 0.20"
Replacement pump:	Pump with Filter
Half Kit:	Pump with inlet strainer, pistol and two different connectors for the pistol (Garden Hose Threaded or Quick Grip Connector)
Full Kit:	Pump, inlet strainer, spray pistol, Klicktite barb port fittings, bulkhead fitting, 7.5m coiled hose & threaded connector for the pistol and coil
KlickTite Connection:	2 Pcs of 3/8" BSP & 1/2" Hose Barb / 2 Pcs of 1/2" NPT & 3/4" Hose Barb / 1 Pcs of 3/4" Garden Hose Thread

