

FLOATING VHF RADIO

FLOATING

Never lose your radio. Floating design and orange core makes retrieving radio easy if dropped overboard.

6 Watt VHF

Select between 1, 3 and 6 Watts for short and long range communication.

ALL NOAA weather channels

Instant access to national All Hazards and weather information, 24 hours a day.

Noise-canceling microphone

Blocks background noise for clearer conversations.

BURP

Vibrates water out of the speaker grill and improves speaker performance.



Features Benefits

- Cutures	Delicites	
FLOATING	Never lose your radio. Floating design and orange core makes retrieving radio easy if dropped overboard.	
Noise Canceling Microphone	Blocks background noise for cleaner conversations.	
6 Watt VHF	Select between 1, 3 and 6 Watts for short and long range communication.	
U.S.A., Canada & International Channels	Allows operation on any of the three (3) different channel maps established for these areas.	
All NOAA Weather Channels	Instant access to national All Hazards and weather information, 24 hours a day.	
Weather Alert	Alerts with an audible tone and visual alarm if threatening weather is nearby.	
BURP	Vibrates water out of the speaker grill and improves speaker performance.	
Submersible	Rated submersible in industry standard JIS7 (IPX7) Specifications.	
External Speaker/ Microphone Jack	Connect Cobra speaker Mic accessories for hip or body worn operation.	
Instant Channel 16	Instant access to channel 16 for emergency situations.	
Unlimited Memory Channels	Allows programming of unlimited channels for easy retrieval or scanning.	
Tri-Watch	Monitors three (3) channels at once - Channel 16 and two (2) user selected channels.	
Scan	Scan all channels to find conversations in progress.	
Memory Scan	Scan channels programmed in memory to find conversations in progress.	
Signal Strength Meter	Shows the strength of the receiving and transmitting signal.	
Button/Key Lock	Locks function buttons/keys to eliminate accidental change of settings.	
Battery Tray With Charge Contacts	Allows charging of batteries in unit.	
Illuminated Function Keys	Allows high visibility of function keys.	
Selectable Key Tone Beep	Key tone press beeps can be turned off to silent operation.	
Large, Illuminated LCD Display	Allows high visibility of display.	
3 Year Warranty (on radio)	For products sold in the U.S.A.	

Included Accessories

included Accessories	
1000 mAh Lithium Ion Rechargeable batteries	Provides extended operating time compared to alkaline batteries with no memory effect.
Locking Desktop Charger with AC/DC adapters	Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. Installs on horizontal or vertical surfaces.
Spring Loaded Swiveling Belt Clip	Secures the radio while on the go. Also removable.

Optional Accessories

CM 110-011	Alkaline Battery Tray.
CM 330-001	Lapel Speaker/Mic.
CM 110-010	1900 mAh Lithium Ion hattery







Floatsif Dr opped

LongerR an ge

BlocksB ackgr oundNois e

Cobra , CobraMarine , Nothing Comes Close to a Cobra , and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation is a trademark of Cobra Electronics Corporation, USA.

©2009 Cobra Electronics Corporation, 6500 West Cortland Street, Chicago, IL 60707, USA

Unit Specifications General

Number of Channels	All: U.S.A., Canadian, International 10 NOAA/Weather Channels
Channel Spacing	25 kHZ
Modulation	5 kHZ
Input Voltage	7.4 VDC
Battery Life: 5:5:90 Stand by	Alkaline Batteries 8 Hours @ 6 Watts, 16 Hours @ I Watt
Battery Requirements	Cobra Battery Pack CM 110-021
Current Drain:	Stand-by: 40mA Receive: 200 mA Transmit: 1.8 A @ High Power, 700 mA @ Low Power
Temperature Range	-20°C to 50°C
Unit Dimensions	4.8" x 2.4" x 1.4" (123 mm x 62 mm x 36 mm) Not including antenna
Unit Weight (Lbs)	0.5 lbs. (228 g) Without batteries

Receiver

Keceivei	
Frequency Range	156.050 to 163.275 MHz
Receiver Type	Double Conversation Super-Heterodyne
Sensitivity:	20dB Quieting: 0.35 uV
	12dB Sinad: 0.30 uV
Adjacent Channel Selectivity	-60 dB
Intermodulation and Rejection	-60 dB
Spurious & Image Rejection	-60 dB
AF Output	250 mW @ 8 0hms

Transmitter

Frequency Range	156.025 to 157.425 MHz
RF Output Power	I, 3 or 6 Watts
Spurious Emissions	-60 dB @ High Power
i e	-55 dB @ Low Power
Frequency Stability	+/-10 ppm
FM Hum & Noise	40 dB

Packaging Specifications

Individual Clam/Box Dimensions	11.4" x 7.5" x 3.1" (330 mm x 190 mm x 80 mm)
Individual Clam/Box Weight	2.2 lbs. (228 g)
Master Pack Qty.	2
Master Pack Dimensions	11.9" x 7.1" x 7.6" (345 mm x 180 mm x 220 mm)
Master Pack Weight	5.15 lbs. (2343 kg)
SKU #	MR HH330 FLT
UPC #	0 28377 20137 0
Master Pack Barcode	1 0028377 20137 5

Specifications subject to change without notice.