

COMPACT SURFACE MOUNT SOLUTION PROVIDING SECURE SCREW TERMINATION WHERE PUSH BUTTON RESET-ONLY CIRCUIT BREAKERS ARE DESIRED

Features

- Quick connect clips allow circuit breakers to snap easily into place and offer secure retention
- Tin-plated copper busses and screw terminals
- Clear insulating cover with square format label recesses, satisfies ABYC/USCG insulation requirements
- Easy to open clip on cover
- Breakouts allow wire access in two directions
- Accepts ring terminals
- Optional push button waterproof boots
- Includes jumpers, for use with 5050 and 5051 to bus multiple circuits together (two included in retail package)
- Circuit breakers sold separately (one included in retail package)

Specifications


Voltage Max. Operating	32V DC
Amperage Max. Operating	32A (per circuit)
Amperage Max. Operating	100A (per block - common source)
Amperage Max. Operating	40A (per jumped circuit group - independent source)
Temperature Min. Operating	-10°C
Temperature Max. Operating	60°C
Breaker Type	Push Button Reset-Only Circuit Breaker with Quick Connect Terminals
Screw Terminal	#8-32 Screws with Captive Star Lock Washer
Mounting	#8 Screw (M4) or #8 Nut
Stud Size	10-32 (M5)

Scan for additional product

NEW

ST CLBCIRCUIT BREAKER BLOCK





PN	Positions	Negative Bus	Source	[A] Height in (mm)	[B] Mounting Centers in (mm)
5050	6	-	Independent	6.69 (169.90)	5.63 (143.0)
5051	12	-	Independent	11.19 (284.20)	10.13 (257.3)
5052	6	Yes	Common	6.69 (169.90)	5.63 (143.0)
5054	12	Yes	Common	11.19 (284.20)	10.13 (257.3)
5049 Jumper (two included in retail package)					





Push Button Reset-Only CLB Circuit Breakers (one included in retail package)



Jumper for independent block, 5050 and 5051 (see table)

Push Button Reset-Only CLB Circuit Breaker Waterproof Boots

4135

Features

- · Protects circuit breaker
- · Replaces dress nut mounting on circuit breakers

Specifications

Thread Material Nickel-Plated Brass
Thread 3/8"-27

 PN
 Description
 Retail Pack

 4135
 Clear
 2



425 Sequoia Drive Bellingham, WA 98226 USA p 360.738.8230 p 800.222.7617 USA and Canada f 360.734.4195

conductor@bluesea.com www.bluesea.com

Specifications subject to change. See bluesea.com for current information. 980016150 Rev. 001