# LoPro Bilge Pumps

LOW PROFILE BILGE PUMPS FOR TIGHT SPACES

## Designed to bring pumping power to tight spaces.

Rule's LoPro Series Bilge Pumps are only 2.25" high. The 900S model features two automated modes. The first one engages the pump when the water level reaches 2" or 1.3" (user choice); and the second one checks for water by briefly turning on the pump every 2.5 minutes. The 900D model requires a float and/or panel switch.

- **Multiple modes of operation.** The 900S features two automated modes of operation.
  - **High or low water sensing mode.** The pump starts when water reaches a 2" level. By turning the motor cartridge upside down, the sensor is at 1.3"
  - **Electronic automatic mode.** The pump automatically turns on every 2.5 minutes to check for water, and if it's detected the pump stays on until the water is gone.
- **Fully rotating discharge body.** The entire body swivels up to 180°, making the pump extremely easy to install.
- **Threaded discharge nozzle.** Multiple ports are available for this pump.
  - ¾" straight, ¾" right angle; 1", 1-1/8"
  - All ports are included in the aftermarket package
- **Backflow prevention.** New tricuspid check valves help prevent backflow.
- **Horizontal or vertical mounting.** The 900S features a variety of mounting options to accommodate the boat's design.



9005

900D

www.rule-industries.com

## LoPro Bilge Pumps low profile bilge pumps for tight spaces

### **Specifications LP900S**

| Voltage: 12VDC                          |          |
|---|----------|
| Flow: 900GPH open flow at 13.6V         |          |
| Amp Draw: 4A approx                     |          |
| Protection: TCO                         |          |
| Port Configuration: 3/4", 1", 1-1/8" St | traight, |
| 90 degree 3/4"                          |          |
| Backflow preventer valve can be use     | ed with  |
| straight fittings                       |          |
| Height: 2.3"                            |          |
| Length: 9.3"                            |          |
| Width: as little as 2.3"                |          |
| UPC: 042237-114075                      |          |
| Model number: LP900S                    |          |

## **Specifications LP900D**

| Voltage: 12VDC                                 |
|--|
| Flow: 900GPH open flow at 13.6V                |
| Amp Draw: 4A approx                            |
| Protection: TCO                                |
| Port Configuration: 3/4", 1", 1-1/8" Straight, |
| 90 degree 3/4″                                 |
| Backflow preventer valve can be used with      |
| straight fittings                              |
| Height: 2.3"                                   |
| Length: 7.6"                                   |
| Width: as little as 2.3"                       |
| UPC: 042237-114082                             |
| Model number: LP900D                           |



Xylem, Inc. USA 100 Cummings Center Ste. 535-N Beverly, MA 01915 Tel: +1 978 281 0440 Fax: +1 978 283 2619 Xylem, Inc. ENGLAND Bingley Road, Hoddesdon Hertfordshire EN11 OBU Tel: +44 (0) 1992 450145 Fax: +44 (0) 1992 467132 Xylem, Inc. CHINA 30/F Tower A 100 Zunyi Road Shanghai, China 200051 Tel: +86-21-2208-2888 Fax: +86-21-2208-2999 Xylem, Inc. GERMANY Oststrasse 28 22844 Norderstedt Tel: +49-40-53 53 73-0 Fax: +49-40-53 53 73-11 Xylem, Inc. ITALY Via Tommaseo, 6 20059 Vimercate, Milano Tel: +39 039 685 2323 Fax: +39 039 666 307

 $\ensuremath{\mathbb{O}}$  2014 Xylem, Inc. All rights reserved. RULE is a trademark of Xylem Inc. or one of its subsidiaries.