

Aftermarket New Product Bulletin #1 Fall 2016+

NEW Integrated Tactile Switch Kit Introduction and Installation Sheet

THIS NEW SWITCH TECHNOLOGY IMPROVES ACCURACY AND INTEGRATES THE CONTROL BOX FUNCTIONALITY INTO THE KEY PAD BEZEL



LENCO ESTIMATES TO START SHIPPING THIS NEW SWITCH KIT TO AFTERMARKET CUSTOMERS NO LATER THAN SEPT 1, 2016

NEW Standard Integrated Tactile Switch Kit Single


12 & 24-Volt Single Actuator Systems - 124SSR-ISK 12 & 24-Volt Single and Dual Actuator Systems - 123SC-ISK






NEW LED Indicator Integrated Tactile Switch Kit Single & Dual

Key Pad Dimensions & Installation Instructions







See the Lenco Marine owners manual for complete switch mounting instructions. lencomarine.com/ownersmanual

Align the center bit of a 2 1/16" (52.39 mm) hole saw with the cross hairs in the center of the desired mounting area and drill straight down through the console, providing additional clearance for switch and electrical connection. Insert the switch into the console cutout hole then tightly screw the Bezel Locknut clockwise onto the backside of the key pad.

NOTE:

This switch has the control box integrated into the back of the switch Key Pad. There is no external control box for this kit. Wiring harness is 30" (76.2 cm) in length from the end of the switch bezel.

