## CM300-005





#### Cobra Positioning System

### External GPS receiver. No more DSC calls without GPS data!

#### Plug-N-Play

Simply plug in to the MR F57 and MR F77 GPS VHF Marine radios. Also plug into your current Cobra Radio with one extra step of connecting power to the GPS.

#### Compatibility

Connects easily to any competitor Radio or Chart Plotter with the included cable.

#### Waterproof

Rated to IPX6 Waterproof specifications.

#### 56 Channel GPS Receiver

Insures reception of all viewable satellites in the sky.

#### **Simple Installation**

Simple "Stick On" under the console. No special tools required for installation.





# CM300-005

<b>Features</b>	Benefits	
Cobra Positioning System	ioning System External GPS receiver. No more DSC calls without GPS data!	
Plug-N-Play	Simply plug in to the MR F57 and MR F77 GPS VHF Marine radios. Also plug into your current Cobra Radio with one extra step of connecting power to the GPS.	
Compatibility	Connects easily to any competitor Radio or Chart Plotter with the included cable.	
Waterproof	Rated to IPX6 Waterproof specifications.	
56 Channel GPS Receiver	Insures reception of all viewable satellites in the sky.	
Simple Installation	e Installation Simple "Stick On" under the console. No special tools required for installation.	
NMEA 0183 Interface	Compliant to NMEA 0183 Version 4.0.	
NMEA Sentences	entences DTM, GGA, GLL, GRS, GSA, GSV, RMC, VTG.	



#### **Unit Specifications General**

ı	General		
	Receiver Type	56 Channels GPS L1C/A SBAS L1C/A QZSS L1C/A GLONASS L10F Galileo E1B/C (when at	vailable)
	Time-To-First-Fix (GPS Only)	Cold Start Warm Start Hot Start Aided Starts	26 seconds 26 seconds < 1 second < 1 second
	Sensitivity (GPS Only)	Tracking & Navigation Reacquisition Cold Start Hot Start	-162 dBm -160 dBm -148 dBm -157 dBm
	Horizontal Position Accuracy	GPS Without SBAS GPS With SBAS	< 2.5 Meters < 2.0 Meters
	Accuracy of Timepulse Signal	RMS 99%	30 nS < 60 nS
	Velocity Accuracy		0.1 m/s
	Heading Accuracy		0.5 Degrees
	Dynamics		< 4 g
	Operational Limits	Altitude 50,000 Mete Velocity 500 m/s	rs
	Unit Dimensions	2.40" H x 2.80" W x 0.71" D (not (not including cable) (61 mm x 71 mm x 18 mm)	
	Unit Weight (Lbs)	6.08 oz. (172.4 g.) with Lithium-Ion Batte	ry

#### **Packaging Specifications**

Individual Package Dimensions	6.30" H x 5.91" W x 0.91" D (160mm x 150mm x 25mm)
Individual Package Weight	TBD (TBD g.)
Master Pack Qty.	4
Master Pack Dimensions	TBD (TBD mm)
Master Pack Weight	TBD (TBD g.)
SKU #	CM300-005
UPC #	0 28377 31375 2
Master Pack Barcode	1 0028377 31375 9

Specifications subject to change without notice.











Cobra®, CobraMarine®, Nothing Comes Close to a Cobra®, and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation™ is a trademark of Cobra Electronics Corporation, USA.

©2014 Cobra Electronics Corporation, 6500 West Cortland Street, Chicago, IL 60707, USA