# **SCENE LIGHTS**

Developed specifically for First Responders and Rescue personnel, LED Scene Lighting by Rigid Industries is an efficient way to light up any area. Available in a variety of sizes and configurations to accommodate different needs and uses, Scene Lighting utilizes the latest in LED technology in a rugged housing that incorporates a thermally optimized heat sink for prolonged, trouble-free use. Scene Lights provide up to 115° horizontal spread for maximum coverage and heavy-duty mounting brackets that enable precise adjustable aiming. Whether it's the scene of a fire or a remote pit in Baja, Scene Lighting provides clear, bright light with minimal amp draw.

RIGID's Scene lights are also available with a durable white finish. Though suitable for marine applications, RIGID's white lighting products are perfect for use anywhere an alternative to black is desired. The distinctive white is a durable UV-resistant powder coated finish with an additional chromate conversion coating for superior corrosion resistance. They feature the same legendary lighting technology and superior build quality as the rest of RIGID's lighting products, providing reliable and efficient lighting on demand.









# **FEATURES**

- 50,000+ Hour Lifespan
- 9-36 V DC
- · Durable UV Polyester Powder Coat
- GORE® Pressure Equalizing Vent
- · Open Leads for Convenient Wiring
- · High-Grade Aluminum Alloy Heatsink
- Integrated Thermal Management System
- Impact Resistant Polycarbonate Lens
- IP68 Compliant Dust / Water Ingress
- Heavy Duty Brackets Included (Excludes 1 x 2)

- Over / Under Voltage Protection
- $\cdot$  Operating Temp -40° F ~ +145° F / -40° C ~ +60° C
- Protected Against RFI / EMI (Excludes 1 x 2)
- Patented Technology
- · Reverse Polarity Protection
- · RoHS Compliant
- SAE J575 Compliant Shock / Vibration
- Up to 115° Beam Pattern
- · White Polycarbonate Reflector with 98% Reflectivity



4 x 4



11.6"


2 x 10



2 x 2



1 x 2



4.04










Also available in Flush Mount











# **BEAM PATTERNS**

Our custom designed graphs are intended to illustrate the beam patterns that our optics produce. First, consider what type of application the light is needed for and then choose what beam pattern best suits your needs. Each beam pattern varies depending on the optic or optic combination you choose. Once you know which beam pattern best suits your needs, refer to the specifications table (A, B, C) to determine how much LUX output you need and which product will best suit your application.





# **AC ALSO AVAILABLE**

ALL HOUSINGS AVAILABLE IN WHITE





- A = LUX AT 10 METERS
- B = BEAM DISTANCE (m) WITH 1 LUX
- C = BEAM DISTANCE (m) WITH .25 LUX

# **SPECIFICATIONS**



### AC VOLTAGE =114-126 VAC

|                              | BEAM<br>DEGREE | MOUNT | BLACK<br>PART NO | WHITE<br>PART NO. | AC/DC | WT.<br>(LBS.) | WATTS | AMP DRAW    | LEDs | *RAW<br>LUMENS | А   | В    | С    | **PEAK BEAM<br>INTENSITY(cd) |
|------------------------------|----------------|-------|------------------|-------------------|-------|---------------|-------|-------------|------|----------------|-----|------|------|------------------------------|
| 1 X 2<br>Scene Light         | 65°            | SM    | 86610            | 86620             | DC    | .53           | 9     | .75 @14VDC  | 3    | 1100           | 7   | 26.4 | 52.7 | 695                          |
| AMBER - 1 X 2<br>SCENE LIGHT | 65°            | SM    | 86630            | 86640             | DC    | .53           | 9     | .75 @14VDC  | 3    | 1100           | N/A | N/A  | N/A  | N/A                          |
|                              | 115°           | SM    | 68151            | 68161             | DC    | 2             | 37    | 2.78 @14VDC | 4    | 4000           | 12  | 35   | 70   | 2143                         |
| 2 X 2<br>SCENE LIGHT         | 115°           | FM    | 68152            | 68162             | DC    | 1.17          | 37    | 2.78 @14VDC | 4    | 4000           | 12  | 35   | 70   | 2143                         |
| SOLINE LIGHT                 | 115°           | FM    | 68371            | 68361             | AC    | 2.1           | 17    | .19 @120V   | 16   | 1541           | 8   | 28   | 57   | 797                          |
| 2 X 10                       | 115°           | SM    | 68131            | 68141             | DC    | 5.36          | 76    | 6 @14VDC    | 9    | 8190           | 22  | 47   | 94   | 2184                         |
| SCENE LIGHT                  | 115°           | SM    | 68351            | 68341             | AC    | 5.5           | 76    | .79 @120V   | 80   | 6293           | 27  | 52   | 104  | 2702                         |
| 4 X 4                        | 115°           | SM    | 68111            | 68121             | DC    | 5.31          | 83    | 5.8 @14VDC  | 9    | 8190           | 22  | 46   | 93   | 2150                         |
| SCENE LIGHT                  | 115°           | SM    | 68321            | 68331             | AC    | 5.1           | 58    | .55 @ 120V  | 64   | 6563           | 24  | 49   | 98   | 2419                         |

<sup>\*</sup> Raw Lumens is based on LED manufacturer specifications.\*\*Distance with .25 lux and Peak Beam Intensity are tested using ANSI/NEMA FL standards. (SM) = Surface Mount, (FM) = Flush Mount



# **LIGHTS COME WITH**

4 x 4 / 2 x 2 / 2 x 10 HOUSING ONLY

- · Mounting Hardware
- · Heavy Duty U-Shape Brackets
- Vibration Isolators

- 1 x 2 HOUSING ONLY
- · Mounting Hardware

DC VERSION ONLY

· 2-Wire Open Lead, No Connector

AC VERSION ONLY

· Standard 110V Outlet Plug