



## NavPro 900 GPS Chart Plotter Series

Two versions available:

NavPro 900C (GPS Chart MSRP \$1199.00)

NavPro 900F (GPS/Chart/Fishfinder MSRP \$1399.00)



- 9" Hi-Res. Hybrid Touch Screen Display
- Innovative new Yoke & Swivel mount
- NMEA-0183 & NMEA2000 Interfacing
- WIFI Interface
- Automatic Software Updates when in WIFI Coverage
- Captain Cloud automatically backs up all User Data to a Free Cloud Based Data backup Service for Waypoints, Marks, Events, and Track memories when in WIFI coverage.
- Mirror Screen Capability via Bluetooth connection allows user to download mirror app to his Android based smart phone and view and control the NavPro 900 from Smart Phone.
- C-Map 4D Cartography – comes bundled with a US Coastal & Rivers Continental 4D card in the box
- Optional dedicated Remote Control Available
- Designed for easy flush mount without any special kit needed
- New CHIRP Sounder with selectable 300w, 600w, & 1kW outputs (NavPro-900F version)
- CHIRP Sounder has scroll back screen memory that allows user to quickly scroll back and pickoff a location to mark on Nav Chart.
- Uses the popular Airmar CHIRP Transducers with TX ID will automatically setup the Sounder transducer interconnect
- Adapters available to allow the unit to be installed on older non-CHIRP transducers. Like 50/200 kHz Dual Frequency transducers and 120kHz Single Freq. transducers. This allows the NavPro 900F to be used to retro fit onto any of the older SI-TEX Transducers. For example, any of the transducers used by the very popular old CVS-106 Sounders. 50/200 & 120kHz
- If customer doesn't have a need for CHIRP sounding he can use a traditional less expensive transducer option
- Internal Hi-Resolution 18Hz 72 Channel GPS Receiver & Antenna
- New User interface makes the unit very easy to operate and navigate with
- Full AIS Integration when interfaced to an AIS Unit

### SPECIFICATIONS:

LCD Display Size 9.0"

Display Brightness 1,100 NITS

Display Resolution 800x480

Touch Screen – Yes, Capacitive Multi-Touch

Keyboard Backlight – Yes

Operating Voltage 10 to 35 VDC

GPS Receiver – Built-In High Resolution 18Hz 72 Channel

GPS/GLONASS

External GPS – Yes, optional via 6 pin Connector

Network Connections – NMEA-2000 (Optional Cable Required)

Dual NMEA-0183 Input/Output Ports

WIFI Connection – Yes

Bluetooth Connection – Yes

IPX6 Waterproof Rating

Operating Temperature range -10°C to +60°C

Dimensions – 10.9" Wide x 6.8" High x 3.7" Deep

2 Year Warranty

### INCLUDE IN THE PACKAGE:

NavPro 900 Display Unit

C-Map 4D Continental Chart Card

Mounting Bracket

Mounting Screws

Combination Power Data Cord

Sun Cover

Installation & Operation manual