



## 1nm comb side, black anodized

101-003-B

1nm comb side, black anodized  
Horizontally mounted with 2,5m cable

Specifications	
Number	101-003-B
Light Color	Red
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>1.2cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010345
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343010348
Connection	2.5m cable

**Specifications**

<b>Current consumption (mA @ 12VDC)</b>	87
---	----

<b>Current consumption (mA @ 24VDC)</b>	48
---	----

<b>Vessel size</b>	Under 12M
--------------------	-----------

<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
-----------------------------	--------------------------

<b>Weight (Kg)</b>	0.63 Kg
--------------------	---------

<b>Weight (Oz)</b>	22.22 Oz
--------------------	----------