



1nm comb side, silver anodized

101-004

1nm comb side, silver anodized
Vertically mounted with 2,5m cable

Specifications	
Number	101-004
Light Color	Red
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>1.2cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010260
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343010263
Connection	2.5m cable

Specifications

Current consumption (mA @ 12VDC) 87

Current consumption (mA @ 24VDC) 48

Vessel size Under 12M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.49 Kg

Weight (Oz) 17.28 Oz