



## 1nm tri-color, black anodized

## 101-005-B

1nm tri-color, black anodized Horizontally mounted with 0,75m cable

| Specifications                   |   |
|----------------------------------|---|
| Number                           | 101-005-B   |
| Light Color                      | Red   |
| Dimensions metric                | Ø92,5mm x 46mm  |
| Certification                    | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="https://www.lopolight.com.under.service-www.lopolight.com.under.service-www.lopolight.com.under.service-www.loport">www.lopolight.com.under.service-www.lopolight.com.under.service-www.loport</a> |
| Dimensions imperial              | Ø3.6" x 1.8"  |
| Approved to                      | COLREG72,EN14744,IEC<br>60945,IACS<br>E10,USCG,ABS,M.E.D.,DNV,LR  |
| Visibility                       | 1nm   |
| Included In Package              | 1 Navigation light,precabled with<br>0.75 meter shielded marine grade<br>cable,Installation guide   |
| Operating temperature            | -25°C to 55°C   |
| Materials                        | Black anodized aluminum 25µ,<br>PMMA lens, A4 stainless steel<br>screws, Epoxy, Polyurethane  |
| Operating Voltage                | 10-32VDC  |
| EAN                              | 5704438010314   |
| IP rating                        | IP68  |
| UPC Code                         | 879343010317  |
| Connection                       | 0.7m cable  |
| Current consumption (mA @ 12VDC) | 150   |
| Current consumption (mA @ 24VDC) | 81  |
| Vessel size                      | Under 12M   |



| Specifications |          |
|----------------|----------|
| Weight (Kg)    | 0.53 Kg  |
| Weight (Oz)    | 18.69 Oz |