



## 2nm 112,5°+ 112,5° combined starboard and port sidelight, vertical mount, with 2,5m cable

201-004

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 20m (39 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multi voltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty..

Vertically mounted with 2,5m cable

Specifications	
Number	201-004
Light Color	Red,Green
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012479
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343012472
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	163
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	90
<b>Vessel size</b>	12-20M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.5 Kg
<b>Weight (Oz)</b>	17.64 Oz