



## 2nm masthead (blk), vert mnt, 0.7m

201-010-B

2nm masthead (blk), vert mnt, 0.7m  
Vertically mounted with 0,75m cable

Specifications	
Number	201-010-B
Light Color	White
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010215
IP rating	IP68
Power draw (W)	2
UPC Code	879343010218
Connection	0.7m cable
Current consumption (mA @ 12VDC)	137

**Specifications**

<b>Current consumption (mA @ 24VDC)</b>	80
---	----

<b>Vessel size</b>	Under 12M
--------------------	-----------

<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
-----------------------------	--------------------------

<b>Weight (Kg)</b>	0.43 Kg
--------------------	---------

<b>Weight (Oz)</b>	15.17 Oz
--------------------	----------