



## 3nm 225° Masthead, black anodized, horizontal mount, with 0,7m cable

201-011KL-B

3nm masthead, black anodized  
Horizontally mounted with 0,75m cable

| Specifications        |  |
|-----------------------|--|
| Number                | 201-011KL-B  |
| Light Color           | White  |
| Dimensions metric     | Ø92,5mm x 46mm   |
| Certification         | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a> |
| Intensity             | >15cd  |
| Dimensions imperial   | Ø3.6" x 1.8"   |
| Approved to           | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR   |
| Visibility            | 3nm  |
| Included In Package   | 1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide  |
| Operating temperature | -25°C to 55°C  |
| Mounting              | Horizontal   |
| Materials             | Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane   |
| Operating Voltage     | 10-32VDC   |
| EAN                   | 5704438012592  |
| IP rating             | IP68   |
| Power draw (W)        | 3  |
| UPC Code              | 879343012595   |
| Connection            | 0.7m cable   |

| Specifications                          |                          |
|---|--------------------------|
| <b>Current consumption (mA @ 12VDC)</b> | 232                      |
| <b>Stock status</b>                     | Usually in stock         |
| <b>Current consumption (mA @ 24VDC)</b> | 127                      |
| <b>Vessel size</b>                      | 12-20M                   |
| <b>Min. feed wire gauge</b>             | 0.5mm <sup>2</sup> AWG22 |
| <b>Weight (Kg)</b>                      | 0.56 Kg                  |
| <b>Weight (Oz)</b>                      | 19.75 Oz                 |