



2nm 135° Yellow towing light, double, black anodized, horizontal mount, with 2,5m cable

201-013ST-B

2nm dbl amber towing, black anodized
Horizontally mounted with 2,5m cables

Specifications	
Number	201-013ST-B
Light Color	Yellow
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010765
IP rating	IP68
Power draw (W)	1,7
UPC Code	879343010768
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	124
Stock status	Made to order
Current consumption (mA @ 24VDC)	71
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.06 Kg
Weight (Oz)	37.39 Oz