



## 3nm 225° Masthead/stern/360° white , silver anodized, horizontal mount, with 0,7m cable

201-021

3nm masthead/stern/360° white , silver anodized  
Horizontal mounted with 0,75m cable

Specifications	
Number	201-021
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>15cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010178
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343010171
Connection	0.7m cable

## Specifications

**Current consumption  
(mA @ 12VDC)** 300

**Stock status** Usually in stock

**Current consumption  
(mA @ 24VDC)** 148

**Vessel size** 12-20M

**Min. feed wire gauge** 0.5mm2 AWG22

**Weight (Kg)** 0.54 Kg

**Weight (Oz)** 19.05 Oz