



3nm 225° Masthead/135° stern/360° white, black anodized, horizontal mount, with 0,7m cable

201-021-B

3nm masthead/stern/360° white, black anodized
Horizontal mounted with 0,75m cable

Specifications	
Number	201-021-B
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009974
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343009977
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	300
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	148
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.54 Kg
Weight (Oz)	19.05 Oz