



## 2nm 135° stern light, single, horizontal mount, silver anodized, with 2,5m cable

301-005

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Horizontally mounted with 2,5m cable

| Specifications        |  |
|-----------------------|--|
| Number                | 301-005  |
| Light Color           | White  |
| Dimensions metric     | Ø92,5mm x 46mm   |
| Certification         | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a> |
| Intensity             | >5.4cd   |
| Dimensions imperial   | Ø3.6" x 1.8"   |
| Approved to           | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR   |
| Visibility            | 2nm  |
| Included In Package   | 1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide  |
| Operating temperature | -25°C to 55°C  |
| Mounting              | Horizontal   |
| Materials             | Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane  |
| Operating Voltage     | 10-32VDC   |
| EAN                   | 5704438012806  |
| IP rating             | IP68   |
| Power draw (W)        | 1,3  |
| UPC Code              | 879343012809   |
| Connection            | 2.5m cable   |

| Specifications                          |                          |
|---|--------------------------|
| <b>Current consumption (mA @ 12VDC)</b> | 110                      |
| <b>Stock status</b>                     | Usually in stock         |
| <b>Lead time</b>                        | 1-2 weeks                |
| <b>Current consumption (mA @ 24VDC)</b> | 50                       |
| <b>Vessel size</b>                      | Under 12M,12-20M,20-50M  |
| <b>Min. feed wire gauge</b>             | 0.5mm <sup>2</sup> AWG22 |
| <b>Weight (Kg)</b>                      | 0.63 Kg                  |
| <b>Weight (Oz)</b>                      | 22.22 Oz                 |