



3nm 135° double stern, silver anodized, horizontal mount, with plug connector

301-105ST

3nm dbl stern, silver anodized
Horizontal mounted on (400-034) CSCD base.

| Specifications | |
|-----------------------|--|
| Number | 301-105ST |
| Light Color | White |
| Dimensions metric | Ø92,5mm x 96,5mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >15cd |
| Dimensions imperial | Ø3.6" x 3.8" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Included In Package | 1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438013292 |
| IP rating | IP68 |
| Power draw (W) | 1,7 |
| UPC Code | 879343013295 |
| Connection | Plug connector |

| Specifications | |
|---|--------------------------|
| Current consumption (mA @ 12VDC) | 130 |
| Stock status | Usually in stock |
| Current consumption (mA @ 24VDC) | 72 |
| Vessel size | Over 50M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 1.32 Kg |
| Weight (Oz) | 46.56 Oz |