



3nm 112,5° double port, silver anodized, horizontal mount, with plug connector

301-109ST

3nm dbl port, silver anodized
Horizontal mounted on (400-034) CSCD base.

Specifications	
Number	301-109ST
Light Color	Red
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010666
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343010669
Connection	Plug connector

Specifications	
Current consumption (mA @ 12VDC)	153
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	92
Vessel size	Over 50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.34 Kg
Weight (Oz)	47.26 Oz