

# SQUALL® LEVER DRAG 2-SPEED

- Lightweight graphite frame and sideplates
- Forged and machined aluminum spool with Line Capacity Rings
- Quick-Shift 2 speed system
- Stainless steel main and pinion gears
- Dura-Drag system
- 4 stainless steel bearings
- Double-dog anti-reverse

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Gear Ratio High/Low	Line Retrieve (in)High/Low	Weight (oz)
SQL16VS	1292936	1090/15 • 725/20 • 540/30	1490/30 • 1040/50 • 865/65	4	20 lbs	26 lbs	4.5:1 / 2.1:1	39/18	38.5
SQL30VSW	1292937	1395/20 • 1035/30 • 595/50	1995/50 • 1660/65 • 1435/80	4	24 lbs	32 lbs	4.2:1 / 1.8:1	41/18	47
SQL50VSW	1292938	1550/30 • 890/50 • 565/80	2485/65 • 2145/80 • 1835/100	4	30 lbs	40 lbs	2.9:1 / 1.5:1	33/17	55.6

• TOPSHOT capacities are located in the Master Capacity Chart.



Our Dura-Drag® material contains a special Phenolic bonding agent that prevents premature breakdown of the carbon fiber material while providing a barrier to water. We then pretreat each drag washer with a special compound developed by PENN® engineers.....say goodbye to jerky drags and lost fish.



The stainless steel gear train in our Squall Lever Drag reels doesn't get much tougher. Machined from stainless steel and drilled out for weight reduction, these gears offer the perfect combination of strength and speed.

