

FATHOM® LEVER DRAG 2-SPEED • FATHOM® LEVER DRAG

FATHOM® LEVER DRAG 2-SPEED

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Max Drag @ Sunset	Gear Ratio High/Low	Line Retrieve (in) High/Low	Weight (oz)
FTH15LD2	1292931	355/12 • 305/15 • 200/20	550/20 • 415/30 • 290/50	5	13 lbs	16 lbs	20 lbs	6.1:1 / 2.8:1	31/14	15.6
FTH25NLD2	1292932	330/20 • 305/25 • 245/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:1	38/19	19.6
FTH25NLD2LH	1422243	330/20 • 305/25 • 245/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:2	38/20	19.6
FTH30LD2	1292933	440/20 • 330/30 • 255/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:1	38/19	20.0
FTH30LD2LH	1422245	440/20 • 330/30 • 255/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.5:1 / 2.7:1	38/19	20.0
FTH40NLD2	1292934	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	5.0:1 / 2.5:1	42/21	25.7
FTH60LD2	1292935	480/40 • 355/50 • 315/60	995/65 • 860/80 • 735/100	5	23 lbs	28 lbs	40 lbs	5.0:1 / 2.5:1	42/21	27.3
FTH15XNLD2	1525512	380/12 • 325/15 • 220/20	595/20 • 450/30 • 310/50	5	23 lbs	33 lbs	40 lbs	5.5:1 / 2.7:1	38/19	18.9
FTH15XNLD2LH	1525513	380/12 • 325/15 • 220/20	595/20 • 450/30 • 310/50	5	23 lbs	33 lbs	40 lbs	5.5:1 / 2.7:1	38/19	18.9

• **TOPSHOT** capacities are located in the Master Capacity Chart.



- Full Metal Body and Sideplates
- Stainless steel main and pinion gear
- Quick-Shift™ 2-speed system
- Dura-Drags™ washers
- 5 shielded stainless steel ball bearings
- Double-dog ratchet anti-reverse
- Line Capacity Rings
- Switchblade™ harness lugs

The stainless steel gear train in our Fathom Lever Drag reels doesn't get much tougher. Machined from stainless steel and drilled out for weight reduction, these gears offer the perfect combination of strength and speed.



FATHOM® LEVER DRAG

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Max Drag @ Sunset	Gear Ratio	Line Retrieve (in)	Weight (oz)
FTH15LD	1338210	355/12 • 305/15 • 200/20	550/20 • 415/30 • 290/50	5	13 lbs	16 lbs	20 lbs	5.3:1	27	15.1
FTH25NLD	1338211	325/20 • 295/25 • 240/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.4
FTH25NLDLH	1422242	325/20 • 295/25 • 240/30	680/30 • 475/50 • 395/65	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.4
FTH30LD	1338212	435/20 • 325/30 • 250/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.8
FTH30LDLH	1422244	435/20 • 325/30 • 250/40	635/50 • 525/65 • 455/80	5	23 lbs	28 lbs	33 lbs	5.3:1	36	19.8
FTH40NLD	1338213	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	4.8:1	40	24.7
FTH40NLDHS	1338214	410/30 • 315/40 • 235/50	785/50 • 655/65 • 565/80	5	23 lbs	28 lbs	40 lbs	7.1:1	60	24.7
FTH60LDHS	1422246	480/40 • 355/50 • 315/60	995/65 • 860/80 • 735/100	5	23 lbs	28 lbs	40 lbs	7.1:1	60	27.3
FTH10XNLD	1525511	470/12 • 405/15 • 270/20	335/20 • 255/30 • 175/50	5	13 lbs	20 lbs	20 lbs	5.3:1	27	14.7

• **TOPSHOT** capacities are located in the Master Capacity Chart.



- Full Metal Body and Sideplates
- Stainless steel main and pinion gear
- Dura-Drags™ washers
- 5 shielded stainless steel ball bearings
- Double-dog ratchet anti-reverse
- Line Capacity Rings

The stainless steel gear train in our Fathom Lever Drag reels doesn't get much tougher. Machined from stainless steel and drilled out for weight reduction, these gears offer the perfect combination of strength and speed.



LEFT HAND MODELS AVAILABLE



HIGH SPEED MODELS AVAILABLE