



**DURABLE. RELIABLE.
BUILT FOR SALTWATER.**



FATHOM™



SQUALL™



HS models designated by red trim

FTH400LP

HS models designated by red trim

SQL200LP



Left Handed - LH



Left Handed - LH

200 / 300 / 400	SIZES AVAILABLE	200 / 300 / 400
6+1	STAINLESS STEEL BEARING SYSTEM	5+1
Aluminum Frame & Crank Side Plate	FRAME MATERIAL	Aluminum Frame
HT-100 Carbon Fiber Drag System	DRAG SYSTEM	HT-100 Carbon Fiber Drag System
✓	SALTWATER SPECIFIC DESIGN	✓
✓	LINE CAPACITY RINGS	✓
✓	HIGH SPEED MODELS AVAILABLE	✓
Dual Action System: Magnetic + Centrifugal	BRAKING SYSTEM	Magnetic
✓	BRASS MAIN GEAR & BEARING SUPPORTED BRONZE PINION	
TiN Coated Level Wind System Gold Anodization	ADDITIONAL FEATURES	

FATHOM™

SQUALL™

FATHOM® LOW PROFILE



FATHOM® LOW PROFILE

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearing	Max Drag	Gear Ratio	Line Retrieve (in)	Weight (oz)
FTH200LP	1525452	225/10 • 180/12 • 130/15	235/20 • 180/30 • 125/50	7	24 lbs	6.6:1	27	8.1
FTH200LPHS	1525453	225/10 • 180/12 • 130/15	235/20 • 180/30 • 125/50	7	24 lbs	8.0:1	33	8.1
FTH200LPLH	1525454	225/10 • 180/12 • 130/15	235/20 • 180/30 • 125/50	7	24 lbs	6.6:1	27	8.1
FTH300LP	1525455	240/12 • 205/14 • 170/17	310/20 • 235/30 • 165/50	7	30 lbs	7.3:1	34	9.2
FTH300LPHS	1525456	240/12 • 205/14 • 170/17	310/20 • 235/30 • 165/50	7	30 lbs	9.2:1	43	9.2
FTH300LPLH	1525457	240/12 • 205/14 • 170/17	310/20 • 235/30 • 165/50	7	30 lbs	7.3:1	34	9.2
FTH400LP	1525458	250/14 • 205/17 • 175/20	285/30 • 235/40 • 200/50	7	25 lbs	6.2:1	34	13.9
FTH400LPHS	1525499	250/14 • 205/17 • 175/20	285/30 • 235/40 • 200/50	7	25 lbs	7.6:1	42	13.9
FTH400LPLH	1525500	250/14 • 205/17 • 175/20	285/30 • 235/40 • 200/50	7	25 lbs	6.2:1	34	13.9



- Full Metal Body and Crank Side Plate
- 6+1 stainless steel bearing system
- HT-100™ drag system
- TiN Coated Level Wind System
- Dual Action Casting Brake
- Line Capacity Rings
- Brass main gear and bearing supported bronze pinion
- Synchronized Drag and Level Wind System on 400 size only

Left Handed - LH

HS models designated by red trim

FTH4000LP