

ZIPK4W2

4 Channel Network Wireless Video Recorder
4 2MP Wireless IP Cameras



Front panel

Rear panel



Key Features

- EZ Wizard – for easy network and system setup
- EZ Search: search events from thumbnails
- EZ Record: set up recording resolutions and recording type
- EZ Copy: copy what you are playing onto a USB flash drive
- EZ App Setup: just scan a QR code with the app to view your cameras on your mobile device

Recorder Features

- Up to 2MP resolution for live view, recording, and playback
- Supports H.264
- Free US-based DDNS service
- Remote monitoring via PC, Mac, Apple TV, Amazon Fire TV, and mobile apps
- 1TB storage

Camera Features

- Supports up to 2MP resolution
- 4.0mm wide angle lens
- IR range up to 65' (built-in IR LEDs)
- Supports H.264 compression
- Wireless range up to 200 ft. (line of sight)
- Built-in mic

What's in the box:

- NVR with 1TB hard drive
- Four 2MP Wireless cameras
- Four 45' DC power extension cables
- One 3ft Ethernet cable
- Remote control (battery included)
- HDMI cable

RESI-CAM®

Camera Specifications

Video	
Imaging Device	2M CMOS (1/2.7")
Effective Pixels	1920(H)x1080(V)
Scanning System	Progressive
Horizontal Resolution	1080p
Min. Illumination	1Lux (IR LED ON)
Lens	
Focal Length	4.0mm
Max. Aperature Ratio	F2.0
Angular Field of View	Diagonal: 102*
Operational	
Shutter Mode	Auto
Gain Control	Auto
White Balance	Auto
Wide Dynamic Range	D-WDR
Digital Noise Reduction	3DNR
PIR	Yes
Mic	Yes
OSD	N/A
Flickerless	Manual (50Hz/60Hz optional)
Day & Night	TRUE D/N, Auto

Night Distance	65ft/20M (Total darkness)
Video Output	Wireless
Wireless range	200' (line-of-sight)
Environmental	
Operating Temperature / Humidity	14°F ~ 122°F / Less than 90% RH Startup: 14°F ~ 122°F
Ingress Protection	IP66
Electrical	
Input Voltage	12V/500mA DC Adaptor

NVR Specifications

Video	
Inputs	4CH Wireless
Resolution	1080p
Multi Screen Display	1/4/SEQ
Live	
Frame Rate	Max. 60fps@1080p Main Stream: 1~15fps@1080p per channel Sub Stream: 1~15fps@640*360 per channel
Resolution	1080p
Multi Screen Display	1/4/SEQ

*Hard drives excluded. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/7/20

NVR Specifications

Operating System

Embedded Linux

Installation Wizard Support

Recording

Compression H.264

Recording Bandwidth Up to 8Mbps (4ch simultaneously, Max. 2Mbps per channel)

Record Rate Main Stream: Max. 15fps@1080p per channel

Mode Manual, Schedule (Continuous/Event), Event (Pre/Post)

Event Video Loss, Motion (Sensitivity Level 1~8)

Overwrite Modes Off/On (Auto/1/3/7/14/30/90 days)

Pre-alarm Min. 1 sec

Post-alarm Up to 5min (30 Sec, 1/2/5min)

Search Mode Date/Time, Event, Motion

Playback Function Fast Forward / backward (2x, 4x, 8x, 16x)
Slow Forward (1/2x, 1/4x, 1/8x, 1/16x)
Step Forward

Live stream Max 60fps @1080p, Max 60fps @640*360

Protocol Support TCP/IP, UDP/IP, RTP(UDP, RTP(TCP), RTSP, NTP, HTTP, DHCP, SMTP, DNS, DDNS, UPNP

Monitoring Web, Mobile, Netview for PC/Mac, Apple TV and Amazon Fire TV

Storage

Internal HDD 1 SATA HDD Max6TB

SD Card 1 SD Card Max 32GB

USB (Back-Up) 2 USB Ports

File Format (Back-Up) H.264, AVI, MP4

Interface

Video

VGA 1 VGA (1,024x768, 1,280x1,024, 1,280x720, 1,440x900)

HDMI 1 HDMI (1,024x768, 1,280x1,024, 1,280x720, 1,440x900)

Audio

Simultaneous Output VGA and HDMI

Inputs/Output N/A (HDMI Output Audio)

Alarm

Port N/A

PTZ Control

RS-485 N/A

Connections

Ethernet 1 RJ45 10/100 Base-T

USB USB 2.0, 2 ports (Front/Rear)

Application Support Mouse, Remote Control

General

Input Voltage/Current 12V/2A DC Adaptor

Operating Temperature/
Humidity 32°F~104°F / 20% ~ 85%RH