



## 5nm 225° Masthead, double, black anodized, horizontal mount, with plug connector

301-011KLST-B

5nm dbl masthead, black anodized  
Horizontal mounted on a CSCD (400-034) base

Specifications	
Number	301-011KLST-B
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>52cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013100
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343013103
Connection	Plug connector
Current consumption (mA @ 12VDC)	320

Specifications	
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	170
<b>Vessel size</b>	20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1.2 Kg
<b>Weight (Oz)</b>	42.32 Oz