



Series 28

LED Navigation Lights in Attractive and Compact Design



Series 28 LED Navigation Lights – Quality That Endures

Series 28 is the latest LED generation of navigation lights in an attractive and compact design. These lights are maintenance-free with sealed for life technology. These lights are available with 316L stainless steel caps for maximum corrosion resistance in harsh environments. The series 28 is specially designed for power boats < 20 m / 65 ft.



Power Supply	12V DC (+/- 10%)
Temp Range	-25°C (-13°F) to +45°C (113°F)
Visibility	2 nm
Light Source	1 or 2 power LED module depending on variants
Electric	1 2V Only, Prewired, 2 wire lead
Optics	With "sealed for life" technology
Mounting	Side-mounts and Deck-mounts, pre-wired with 150 mm (6") cable 2 \times 0.25 mm2/ AWG 22
Housing	Polycarbonate black housing, seawater resistant, UV-resistant, non-corrosive and non-magnetic, impact and shock resistant. Steel cap on the top
Approvals	USCG, A-16, ISO 19009
Deckmount Features	Tell-Tale indicator light

Â in al

4



5







Get more information here:

6





Ref.		Description	Vessels	Wattage	Visibility	Housing Color	Mounting	Voltage	Article Number (OEM)	Article Number (Packaged)
1	135°	Stern	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Side- mount	12V	3728001000	28500-7
	135°	Stern	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Side- mount	12V	3728002000	28501-7
2	A	Starboard	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Side- mount	12V	3726001000	28202-7
	Reg	Starboard	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Side- mount	12V	3726002000	28203-7
0		Port	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Side- mount	12V	3727001000	28302-7
3		Port	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Side- mount	12V	3727002000	28303-7
4		Starboard	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Deck- mount	12V	3729002000	28200-7
		Starboard	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Deck- mount	12V	3729005000	28201-7
5		Port	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Deck- mount	12V	3729003000	28300-7
		Port	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Deck- mount	12V	3729006000	28301-7
6		Bi-Color	< 20 m / < 65 ft.	2 W	2 nm	Polycarbonate, Black	Deck- mount	12V	3729001000	28100-7
		Bi-Color	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Deck- mount	12V	3729004000	28105-7
7		Bi-Color, Hideaway	< 20 m / < 65 ft.	2 W	2 nm	Stainless steel	Deck- mount	12V	3730001000	28600-7

© Glamox October 2020