



## 2nm 360° white, double, with 0,7m cable

200-012G2ST

2nm dbl 360° white

Horizontally mounted with 2 x 0,75m cables

### Specifications

<b>Number</b>	200-012G2ST
<b>Light Color</b>	White
<b>Dimensions metric</b>	Ø92,5mm x 68mm
<b>Certification</b>	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
<b>Intensity</b>	>5.4cd
<b>Dimensions imperial</b>	Ø3.6" x 2.7"
<b>Approved to</b>	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
<b>Visibility</b>	2nm
<b>Included In Package</b>	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
<b>Operating temperature</b>	-25°C to 55°C
<b>Mounting</b>	Horizontal
<b>Materials</b>	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
<b>Operating Voltage</b>	10-32VDC
<b>EAN</b>	5704438012080
<b>IP rating</b>	IP68
<b>Power draw (W)</b>	2,6
<b>UPC Code</b>	879343012083
<b>Connection</b>	0.7m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	167
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	110
<b>Vessel size</b>	Under 12M,12-20M,20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.59 Kg
<b>Weight (Oz)</b>	20.81 Oz