



2nm 360° white/strobe, silver anodized

200-012G2S

2nm 360° white/strobe, silver anodized
Horizontally mounted with 0,75m cable

Specifications	
Number	200-012G2S
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438020597
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343020729
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	167
Stock status	Not usually in stock
Current consumption (mA @ 24VDC)	110
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0 Kg
Weight (Oz)	0.00 Oz