



2nm 112,5°+ 112,5° combined starboard and port sidelight, horizontal mount, with 2,5m cable

201-003-REVERSE

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 20m (39 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multi voltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty..

Horizontal mounted with 2.5m cable

Specifications	
Number	201-003-REVERSE
Light Color	Red,Green
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012462
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343012465
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	163
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	90
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.65 Kg
Weight (Oz)	22.93 Oz