



## 2nm Tricolor, anchor w/strobe, black anodized, horizontal mount, with 0,7m cable

201-007G2S-B

2nm Tricolor, anchor w/strobe. black anodized  
Horizontal mounted with 0.75m cable

Specifications	
Number	201-007G2S-B
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438011892
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343011895
Connection	0.7m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	213
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	123
<b>Vessel size</b>	12-20M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1 Kg
<b>Weight (Oz)</b>	35.27 Oz