



2nm Tricolor, anchor w/strobe, silver anodized, horizontal mount, with 30m cable

201-007G2S 30M

2nm tri-color/anchor/strobe, silver anodized
Horizontal mounted with 30m cable

Specifications	
Number	201-007G2S 30M
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438011724
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343011727
Connection	30m cable

Specifications	
Current consumption (mA @ 12VDC)	213
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	123
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	2.3 Kg
Weight (Oz)	81.12 Oz