



## 2nm Tricolor with anchor and Windex light

## 201-007G2W

2nm Tricolor with anchor and Windex light 3 functions, all separate: Tri-color, Anchor, Windex light Silver aluminium housing 0,75 m 4-core cable.

Specifications	
Number	201-007G2W
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 86mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a 3.3"<="" href="https://www.lopolight.com.under-Service-www.lopolight.com.under-Service&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Intensity&lt;/th&gt;&lt;th&gt;&gt;5.4cd&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Dimensions imperial&lt;/th&gt;&lt;th&gt;Ø3.6" th="" x=""></a>
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438020634
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343020767
Connection	0.7m cable



Specifications	
Current consumption (mA @ 12VDC)	213
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	123
Vessel size	12-20M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0 Kg
Weight (Oz)	0.00 Oz