



3nm 225° Masthead+6W decklight, black anodized, vertical mount, with 15m cable

201-011DLX-B 15M

3nm masthead+6W decklight, black anodized
Vertically mounted with 15m cable

Specifications	
Number	201-011DLX-B 15M
Light Color	White
Dimensions metric	54 x 38,7 x 72,2
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	2.1" x 1.5" x 2.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012585
IP rating	IP68
Power draw (W)	3
UPC Code	879343012588
Connection	15m cable

Specifications	
Current consumption (mA @ 12VDC)	232
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	127
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.43 Kg
Weight (Oz)	50.44 Oz