



3nm 225° Masthead, double, silver anodized, vertical mount, with 0,7m cable

201-011ST

3nm dbl masthead, silver anodized
Vertically mounted with 0,75m cables

Specifications	
Number	201-011ST
Light Color	White
Dimensions metric	92,5 x 88,6 x 85
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	3.6" x 3.4" x 3.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010925
IP rating	IP68
Power draw (W)	3
UPC Code	879343010928
Connection	0.7m cable
Current consumption (mA @ 12VDC)	232

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	127
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.01 Kg
Weight (Oz)	35.62 Oz