



2nm 360° Red, silver anodized, horizontal mount, with 15m cable

200-014G2-B 15M

2nm 360° Red, silver anodized
2nm 360° Red, silver anodized

| Specifications | |
|-----------------------|--|
| Number | 200-014G2-B 15M |
| Light Color | Red |
| Dimensions metric | Ø92,5mm x 46mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support |
| Intensity | >5.4cd |
| Dimensions imperial | Ø3.6" x 1.8" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 2nm |
| Included In Package | 1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide |
| Operating temperature | -25°C to 55°C |
| Mounting | Horizontal |
| Materials | Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 10-32VDC |
| EAN | 5704438019188 |
| IP rating | IP68 |
| Power draw (W) | 2,1 |
| UPC Code | 879343019310 |
| Connection | 0.7m cable |

| Specifications | |
|---|--------------------------|
| Current consumption (mA @ 12VDC) | 150 |
| Stock status | Not usually in stock |
| Current consumption (mA @ 24VDC) | 85 |
| Vessel size | Under 12M,12-20M,20-50M |
| Min. feed wire gauge | 0.5mm ² AWG22 |
| Weight (Kg) | 0 Kg |
| Weight (Oz) | 0.00 Oz |