



## 2nm 360° Red, double, black anodized, with 0,7m cable

200-014G2ST-B

2nm dbI 360° Red, black anodized  
horizontal mounted

Specifications	
Number	200-014G2ST-B
Light Color	Red
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.7"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438016767
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343016791
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150

**Specifications**

<b>Stock status</b>	Usually in stock
---------------------	------------------

<b>Current consumption (mA @ 24VDC)</b>	85
---	----

<b>Vessel size</b>	Under 12M,12-20M,20-50M
--------------------	-------------------------

<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
-----------------------------	--------------------------

<b>Weight (Kg)</b>	0.6 Kg
--------------------	--------

<b>Weight (Oz)</b>	21.16 Oz
--------------------	----------