



## 2nm dbl 360° Green, silver anodized

## 200-015G2ST

2nm dbl 360° Green, silver anodized Horizontal mounted with 0.75m cables

Specifications	
Number	200-015G2ST
Light Color	Green
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a 2.7"<="" href="https://www.lopolight.com/www.lopolig&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Intensity&lt;/th&gt;&lt;th&gt;&gt;5.4cd&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Dimensions imperial&lt;/th&gt;&lt;th&gt;Ø3.6" th="" x=""></a>
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
EAN	5704438022270
IP rating	IP68
UPC Code	879343022402
Connection	0.7m cable
Current consumption (mA @ 12VDC)	182
Current consumption (mA @ 24VDC)	176
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	0 Kg



Specifications	
Weight (Oz)	0.00 Oz